

ELAN EL-600-IWLCR-5

ELAN®

600 Series LCR In-Wall Speakers

(Sold Individually)



Exceptional Clarity, Resolution and Dynamics.

A multipurpose speaker with step-up performance, the EL-600-IWLCR-5 includes an upgraded injection molded polypropylene cone woofer and a pivoting 1" silk dome tweeter that's perfect for home theater as a left, center, or right speaker.



EL-600-IWLCR-5 In-Wall Speakers

ORDER NO. EL-600-IWLCR-5

600 SERIES

▪ Room Filling Sound

Low Crossover points and woofers that are mounted as close to the surface as possible delivers the widest dispersion and best sound quality possible.

▪ Silky Smooth Highs

Silk dome tweeters reduce the severity of break-up modes resulting in silky smooth sound which is pleasing to the ear—even at high volumes.

▪ Tilt Tweeter

The tilting tweeter mechanism allows you to direct sound to the listening area and maintains high frequency performance even when the speaker is mounted in less than ideal locations.

▪ Thin is In

A thin-bezel magnetic grille ensures a secure fit, pleasing aesthetic and with a one-step paint process, it fits universally into almost any décor.

▪ Secure Connection

All ELAN speakers feature spring loaded binding posts that provide a secure, worry-free connection in the wall or ceiling.

▪ Lifetime Warranty

Feel confident that all ELAN architectural speakers are backed by a limited lifetime warranty.

SPECIFICATIONS	
Woofer Size	Dual 5.25" (130mm)
Woofer Construction	Injection Molded Polypropylene Cone
Tweeter	1" (25mm) Pivoting Silk Dome
Frequency Response	48Hz-20kHz
Impedance	8 Ohms
Power Handling	110 Watts
Sensitivity	90 dB
Timbre	Timbre-Matched to all 600 Series Speakers
Dimensions	15.6" (396mm) Width x 7.76" (197mm) Height x 3.9" (99mm) Depth
Hole Cutout Dimensions	6.5" (157.2mm) Width x 14.5" (369mm) Height
Mounting Depth	3.8" (96mm)



Use Pre-Construction Bracket

EL-PCB-IWLCR-5



ELAN®

Your world, made simple.™

www.elanhomesystems.com