

ELAN EL-800-IC-6

ELAN®

800 Series In-Ceiling Speakers

(Sold In Pairs)



Exceptional Clarity, Resolution and Dynamics

Whether it's high-performance distributed audio or home theater, the EL-800-IC-6 is the perfect choice for discerning customers. Better clarity, resolution and dynamics are achieved via a graphite-injected polypropylene cone woofer and 1" aluminum dome tweeter. Front-mounted vocal and tweeter enhancement switch enable increased vocal clarity, enhanced dialogue and adjustment of post-installation tweeter performance.



EL-800-IC-6 In-Ceiling Speakers

ORDER NO. EL-800-IC-6

800 SERIES

▪ Dynamic Room Filling Sound

Low Crossover points and a light-weight graphite injected polypropylene cone woofer that's mounted as close to the surface as possible delivers dynamic sound with the widest dispersion possible.

▪ Quick, Responsive Highs

Aluminum dome tweeters are lightweight, strong and respond instantaneously to changes in music or movies.

▪ Tilt Tweeter

The tilting tweeter mechanism allows you to direct sound to the listening area and maintains high frequency performance even when the speaker is mounted in less than ideal locations.

▪ Vocal and Tweeter Enhancement Switches

Easily adjust tweeter performance or enhance the dialogue in movies via the Vocal and Tweeter Enhancement Switches.

▪ Thin is In

A thin-bezel magnetic grille ensures a secure fit, pleasing aesthetic and with a one-step paint process, it fits universally into almost any décor.

▪ Easy-Grip Tweeter Bridge

We know you do it! Installing speakers above your head requires a sturdy grip point and the ELAN Tweeter bridge ensures you have one. We even protect the tweeter from accidental finger pokes.

▪ Dimpled Baffle Design

The dimpled baffle design eliminates annoying echoes and increases dispersion by reducing the focusing action of the concave baffle. The result is crystal-clear room filling sound.

▪ Secure Connection

All ELAN speakers feature spring loaded binding posts that provide a secure, worry-free connection in the wall or ceiling.

SPECIFICATIONS	
Woofer Size	6-1/2" (160mm)
Woofer Construction	Graphite Injected Polypropylene Cone
Tweeter	1" (25 mm) Pivoting Aluminum Dome
Frequency Response	50Hz-20kHz
Impedance	8 Ohms
Power Handling	120 Watts
Sensitivity	88 dB
Timbre	Timbre-Matched to all 800 Series Speakers
Dimensions	9.625" (237mm) Diameter x 3.94" (100 mm) Depth
Hole Cutout Dimensions	8.25" (210mm) Diameter
Mounting Depth	3.81" (97mm)



Use Pre-Construction Bracket

EL-PCB-IC-6



ELAN®

Your world, made simple.™

www.elanhomesystems.com