

ELAN EL-800-IC-8

ELAN®

800 Series In-Ceiling Speakers

(Sold In Pairs)



Exceptional Clarity, Resolution and Dynamics

Whether it's high-performance distributed audio or an exceptional home theater experience, the EL-800-IC-8 is the perfect choice for discerning customers. Better clarity, resolution and dynamics are achieved with the graphite-injected polypropylene cone woofer and pivoting 1" aluminum dome tweeter. Increased vocal clarity, enhanced dialogue and adjustment of post-installation tweeter performance are enabled with the front-mounted vocal and tweeter enhancement switches.



EL-800-IC-8 In-Ceiling Speakers

ORDER NO. EL-800-IC-8

800 SERIES

▪ Dynamic Room Filling Sound

Low Crossover points and a light-weight graphite injected polypropylene cone woofer that's mounted as close to the surface as possible delivers dynamic sound with the widest dispersion possible.

▪ Quick, Responsive Highs

Aluminum dome tweeters are lightweight, strong and respond instantaneously to changes in music or movies.

▪ Tilt Tweeter

The tilting tweeter mechanism allows you to direct sound to the listening area and maintains high frequency performance even when the speaker is mounted in less than ideal locations.

▪ Vocal and Tweeter Enhancement Switches

Easily adjust tweeter performance or enhance the dialogue in movies via the Vocal and Tweeter Enhancement Switches.

▪ Thin is In

A thin-bezel magnetic grille ensures a secure fit, pleasing aesthetic and with a one-step paint process, it fits universally into almost any décor.

▪ Easy-Grip Tweeter Bridge

We know you do it! Installing speakers above your head requires a sturdy grip point and the ELAN Tweeter bridge ensures you have one. We even protect the tweeter from accidental finger pokes.

▪ Dimpled Baffle Design

The dimpled baffle design eliminates annoying echoes and increases dispersion by reducing the focusing action of the concave baffle. The result is crystal-clear room filling sound.

▪ Secure Connection

All ELAN speakers feature spring loaded binding posts that provide a secure, worry-free connection in the wall or ceiling.

▪ Lifetime Warranty

Feel confident that All ELAN Architectural speakers are backed by a limited lifetime warranty

SPECIFICATIONS	
Woofer Size	8" (200mm)
Woofer Construction	Graphite Injected Polypropylene Cone
Tweeter	1" (25mm) Pivoting Aluminum Dome
Frequency Response	48Hz-20kHz
Impedance	8 Ohms
Power Handling	130 Watts
Sensitivity	90 dB
Timbre	Timbre-Matched to all 800 Series Speakers
Dimensions	10.8" (275mm) Diameter x 4.65" (118mm) Depth
Hole Cutout Dimensions	9.75" (248mm) Diameter
Mounting Depth	4.53" (115mm)



Use Pre-Construction Bracket

EL-PCB-IC-8



ELAN®

Your world, made simple.™

www.elanhomesystems.com