



Product description:

Wolsey LTE Masthead Amplifier Kit

- F-Connector Masthead Amplifier and Power Supply Kit
- 1 Input 4 Output
- 10-25 dB Variable Gain
- Weatherproof housing
- Fully screened enclosure

**LTE WFAV 425 - 1 Input - Wideband Masthead Amplifier
370562**

Technical Specifications

ORDER INFORMATION

EAN Number 5702663705623

CHARACTERISTICS

Max. Output level @ 60 dB IMD 85 dBμV

FREQUENCY

Input 1 - frequency 470...790 MHz

Input 1 - band UHF (T)

Input 1 - channels 21...60

GAIN

Input 1 - gain 10-25 dB

Input 1 - noise figure	<2.2 dB
------------------------	---------

RETURN LOSS

Return Loss	10 Typ dB
-------------	-----------

OPERATIONAL

DC Operating voltage	12 VDC
----------------------	--------

DC Current consumption (typ.)	100 mA
-------------------------------	--------

CONNECTORS

Number of inputs	1
------------------	---

Number of outputs	4
-------------------	---

Connector Type	F-female
----------------	----------

MECHANICAL

Colour	Black
--------	-------

Height (mm)	215 mm
-------------	--------

Depth (mm)	60 mm
------------	-------

Width (mm)	120 mm
------------	--------

Remarks	Kit includes WPS 100 Power Supply, 12VDC, 100mA Max Fully screened
---------	--

Packaging Volume	0,002 m3
------------------	----------

Net Weight	0,550 kg
------------	----------

Tara Weight	0,065 kg
-------------	----------

Total Weight	0,615 kg
--------------	----------

Packaging Height	0,070 m
------------------	---------

Packaging Width	0,220 m
-----------------	---------

Packaging Depth	0,120 m
-----------------	---------