

# Technical Data

## AT77 All Weather PVC Electrical Insulation Tape

### General description

A PVC film coated with an aggressive rubber-resin adhesive.

- Flame retardant.
- Self-extinguishing.
- Good low temperature performance.
- Flexible.
- Conformable to awkward shapes.
- Good abrasion resistance.
- Good resistance to ageing.
- UV resistant.
- Non-corrosive adhesive.

### Specification

Certification\* to the following standards may be available on request, BS3887 :1991 and BS EN 60454/Type 6 (Formerly BS 3924)

### Technical Details

Typical values

Thickness	0.19mm
Breaking Load	30 N/cm
Elongation	250%
Adhesion	
Steel	2.6 N/cm
Self	2.5 N/cm
Moisture Vapour Permeability	40g/m <sup>2</sup> /24 hrs
Flame Retardancy	Self-extinguishing
Breakdown Voltage	10 kV
Service Temp	-18°C to +80°C
Application Temp	-10°C to +80°C

\*Standard charge for certificate:£25.00.



### NOTE

Except where indicated otherwise, the above figures are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

### STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

 **ADVANCE**  
adhesive tapes



BS EN ISO 9002  
Q05206



INVESTOR IN PEOPLE

### AFERA

Association des Fabricants Européens de  
Rubans Auto-Adhésifs.