

Part Number: 120452C-LSOH-VLT-305
Description: WEBNET Cat 6 U/UTP 4pair Low
 Smoke Non-Halogen (LSNH) Violet



Product Construction

Conductor Material : Bare Copper
 Insulation Material : High Density Polyethylene (HDPE)
 Number of Pairs : 4
 Pair Colours : Blue, Blue/White; Orange, Orange/White,
 Green, Green/White; Brown, Brown/White
 Sheath Material : Low Smoke Non-Halogen (LSNH)
 Sheath Colour : Violet



Mechanical Characteristics

Overall Diameter : 5.9mm ± 0.30mm
 Temperature Range : Fixed -10°C to +60°C Flexing 0°C to +50°C
 Bend Radius : Fixed 4 x Overall Diameter Flexing 8 x Overall Diameter
 Weight : 40 kg/km

Electrical Characteristics

Max. Conductor DC Resistance : ≤ 9.5 Ω/km @ 20°C
 Max. Resistance Unbalanced : < 2.5%
 Max. Insulation Resistance : > 5000 MΩ x m
 Mutual Capacitance : < 5.6 nF/100m
 Capacitance Unbalanced : 1600 pF/km
 Impedance @ 100 MHz : 100 Ω ± 5
 Velocity of Propagation : 65 %
 Delay Skew : < 45 ns / 100m
 Dielectric Strength - DC : 1kV for 1minute

Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	PS - NEXT (dB)	ACRF (dB)	PS-ACRF (dB)	Return Loss (dB)
1	≤ 2.0	≥ 74.3	≥ 72.3	≥ 67.8	≥ 64.8	20.0
4	≤ 3.8	≥ 65.3	≥ 63.3	≥ 55.8	≥ 52.8	23.0
8	≤ 5.3	≥ 60.8	≥ 58.8	≥ 49.7	≥ 46.7	24.5
10	≤ 6.0	≥ 59.3	≥ 57.3	≥ 47.8	≥ 44.8	25.0
16	≤ 7.6	≥ 56.2	≥ 54.2	≥ 43.7	≥ 40.7	25.0
20	≤ 8.5	≥ 54.8	≥ 52.8	≥ 41.8	≥ 38.8	25.0
25	≤ 9.5	≥ 53.3	≥ 51.3	≥ 39.8	≥ 36.8	24.3
31.25	≤ 10.7	≥ 51.9	≥ 49.9	≥ 37.9	≥ 34.9	23.6
62.5	≤ 15.4	≥ 47.4	≥ 45.4	≥ 31.9	≥ 28.9	21.5
100	≤ 19.8	≥ 44.3	≥ 42.3	≥ 27.8	≥ 24.8	20.1
200	≤ 29.0	≥ 39.8	≥ 37.8	≥ 21.8	≥ 18.8	18.0
250	≤ 32.8	≥ 38.3	≥ 36.3	≥ 19.8	≥ 16.8	17.3

Performance @ 20°

Certifications & Standards

Flame Retardancy : BS EN 60332-1-2 Certification : HDBaseT
 Low Smoke : BS EN 61034-2 RoHS 3 Compliant : Yes
 Halogen Gas : BS EN 60754-1&2 REACH Compliant : Yes
 Manufactured in Accordance to : TIA/EIA 568-C.2, IEC 11801 Class E, EN 50288-6-1, ISO/IEC 61156-5, EN 50173-1
 CE CPR Classification : Cca s1a, d0, a1 EN 50575:2014+A1:2016



Publication Date: 30/01/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.