

**Part Number:** 120452E-LSOH-BLU-305-01  
**Description:** WEBNET Cat 6 U/UTP 4pair Low  
 Smoke Non-Halogen (LSNH) Blue



**Product Construction**

Conductor Material : Bare Copper  
 Insulation Material : High Density Polyethylene (HDPE)  
 Number of Pairs : 4  
 Pair Colours : Blue, Blue/White; Orange, Orange/White,  
 Green, Green/White; Brown, Brown/White  
 Sheath Material : Low Smoke Non-Halogen (LSNH)  
 Sheath Colour : Blue



**Mechanical Characteristics**

Overall Diameter : 5.9mm ± 0.30mm  
 Temperature Range : Fixed -10°C to +60°C      Flexing 0°C to +50°C  
 Bend Radius : Fixed 4 x Overall Diameter      Flexing 8 x Overall Diameter  
 Weight : 40 kg/km

**Electrical Characteristics**

Max. Conductor DC Resistance : ≤ 9.5 Ω/km @ 20°C  
 Max. Resistance Unbalanced : < 2.5%  
 Max. Insulation Resistance : > 5000 MΩ x m  
 Mutual Capacitance : < 5.6 nF/100m  
 Capacitance Unbalanced : 1600 pF/km  
 Impedance @ 100 MHz : 100 Ω ± 5  
 Velocity of Propagation : 65 %  
 Delay Skew : < 45 ns / 100m  
 Dielectric Strength - DC : 1kV for 1minute

Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	PS - NEXT (dB)	ACRF (dB)	PS-ACRF (dB)	Return Loss (dB)
1	≤ 2.0	≥ 74.3	≥ 72.3	≥ 67.8	≥ 64.8	20.0
4	≤ 3.8	≥ 65.3	≥ 63.3	≥ 55.8	≥ 52.8	23.0
8	≤ 5.3	≥ 60.8	≥ 58.8	≥ 49.7	≥ 46.7	24.5
10	≤ 6.0	≥ 59.3	≥ 57.3	≥ 47.8	≥ 44.8	25.0
16	≤ 7.6	≥ 56.2	≥ 54.2	≥ 43.7	≥ 40.7	25.0
20	≤ 8.5	≥ 54.8	≥ 52.8	≥ 41.8	≥ 38.8	25.0
25	≤ 9.5	≥ 53.3	≥ 51.3	≥ 39.8	≥ 36.8	24.3
31.25	≤ 10.7	≥ 51.9	≥ 49.9	≥ 37.9	≥ 34.9	23.6
62.5	≤ 15.4	≥ 47.4	≥ 45.4	≥ 31.9	≥ 28.9	21.5
100	≤ 19.8	≥ 44.3	≥ 42.3	≥ 27.8	≥ 24.8	20.1
200	≤ 29.0	≥ 39.8	≥ 37.8	≥ 21.8	≥ 18.8	18.0
250	≤ 32.8	≥ 38.3	≥ 36.3	≥ 19.8	≥ 16.8	17.3

Performance @ 20°

**Certifications & Standards**

Flame Retardancy : BS EN 60332-1-2      Certification : HDBaseT  
 Low Smoke : BS EN 61034-2      RoHS 3 Compliant : Yes  
 Halogen Gas : BS EN 60754-1&2      REACH Compliant : Yes  
 Manufactured in Accordance to : TIA/EIA 568-C.2, IEC 11801 Class E, EN 50288-6-1, ISO/IEC 61156-5, EN 50173-1  
 UKCA CPR Classification : Eca BS EN 50575:2014+A1:2016



Publication Date: 30/01/2023  
 Revision Number: 2.0  
 Written by: GB  
 Authorised by: GB

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.