

TDA 65LG RAL 7035, singlepack

Art. Number 120505



TRIAX TD Dishes The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivalled build quality, whether Steel or Aluminium
 - Hot-dip galvanized steel OR long lasting Aluminium - for extra corrosion protection
 - TRIAX's unique cable protection system
 - Every part, every accessory is weatherproofed
 - 2 years corrosion warranty
 - 5 years functionality warranty
- Outstanding performance
 - High gain for an exceptional signal
- Quick and easy installation
 - One-click mounting system
 - Self-locking screw & nuts
- Logistic friendly
 - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

[Click here](#) to see our guide on how to install TRIAX satellite dishes.

Technical Specifications

ORDER INFORMATION

EAN Number

5702661205057

Technical Specifications

CHARACTERISTICS

Elevation range °	0...90 °
F/D ratio	0,62
G/T LNB 0.7 dB/K	16.0 dB/K
Offset angle °	26 °
X-polarisation dB	≤ -25 dB

FREQUENCY RANGE

Frequency range GHz	10.7...12.75 GHz
-----------------------	------------------

GAIN

Gain @ 11.7 GHz dBi	36 dBi
-----------------------	--------

MECHANICAL

Arm Colour	Raw
Beamwidth °	3.1 °
Colour	RAL 7035 - Light grey
Product Depth mm	682 mm
Packaging Depth m	0.740 m
Packaging Height m	0.105 m
Total Weight kg	3.450 kg
Packaging Width m	0.713 m
Height (cm) cm	66 cm
Product Height mm	40 mm
LNB holder	40
Main material	Aluminium
Mast bracket diameter mm	30...60 mm
Net Weight kg	2.350 kg
Packing QTY	1
Reflector type	Offset
Tara Weight kg	1.100 kg
Packaging Volume m3	0.050 m3
Width (cm) cm	60 cm
Product Width mm	623 mm