



TDS 80A RAL 7016, bulk pack

Art. Number 120510



TRIAX TD Dishes The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivaled build quality, whether Steel or Aluminium
 - Hot-dip galvanized steel OR long lasting Aluminium for extra corrosion protection
 - TRIAX's unique cable protection system
 - Every part, every accessory is weatherproofed
 - 2 years corrosion warranty
 - 5 years functionality warranty
- Outstanding performance
 - High gain for an exceptional signal
- Quick and easy installation
 - One-click mounting system
 - Self-locking screw & nuts
- Logistic friendly
 - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

<u>Click here</u> to see our guide on how to install TRIAX satellite dishes.

Technical Specifications

ORDER INFORMATION

EAN Number 5702661205101

triax.com



connecting the future

Technical Specifications

rechinda Opecindadorio	
CHARACTERISTICS	
F/D ratio	0,62
G/T LNB 0.7 dB/K	17.3 dB/K
X-polarisation dB	≤ -27 dB
Offset angle °	25.6 °
Elevation range °	090 °
FREQUENCY RANGE	
Frequency range GHz	10.712.75 GHz
GAIN	
Gain @ 11.7 GHz dBi	37,5 dBi
MECHANICAL	
Height (cm) cm	79 cm
Width (cm) cm	71 cm
LNB holder	40
Mast bracket diameter mm	3260 mm
Reflector type	Offset
Beamwidth °	2.6 °
Windload @42 m/s N	619 N
Main material	Galvanized steel (hot-dip)
Arm Colour	Raw
Colour	RAL 7016 - Anthracite grey
Packing QTY	200
Packaging Height m	0.011 m
Packaging Width m	0.710 m
Packaging Depth m	0.790 m
Packaging Volume m3	0.006 m3
Net Weight kg	4.420 kg
Tara Weight kg	0.095 kg
Total Weight kg	4.515 kg

14-04-2022 2/2 triax.com