## Technical Document WEB400 50ohm Low Loss Coaxial Cable PE Black



Part Number: 140400F-BLK

Description: WEB400 50ohm Low Loss Coaxial

Cable PE Black

Product Construction

Conductor Material : Copper Clad Aluminium
Conductor Stranding : Solid, 1/2.74mm
Dielectric Material : Foam Polyethylene (FPE)
Dielectric Diameter : 7.24mm ± 0.10

Screening 1 : Overall Bonded Aluminium Foil

Screening 1 Coverage : > 100%

Screening 2 : Tinned Copper Wire Braid

Screening 2 Coverage :  $> 90\% \pm 3$ Sheath Material : Polyethylene (PE)

Sheath Colour : Black

Mechanical Characteristics

Overall Diameter :  $10.3 \text{mm} \pm 0.20 \text{mm}$ 

Temperature Range : Fixed -15°C to +70°C Flexing -5°C to +70°C

Bend Radius : 10 x Overall Diameter

Weight : 120kg/km

**Electrical Characteristics** 

Inner Conductor DC Resistance :  $\leq 4.8 \ \Omega/km \ @ 20^{\circ}C$ Outer Conductor DC Resistance :  $\leq 5.9 \ \Omega \ /km \ @ 20^{\circ}C$ 

Attenuation @20°C

Frequency (MHz)	Attenuation (per 100m)	Attenuation (per 100ft)	Power kW
30	≤ 2.2 dB	≤ 0.7 dB	3.33
50	≤ 2.9 dB	≤ 0.9 dB	2.57
150	≤ 5.0 dB	≤ 1.5 dB	1.47
220	≤ 6.1 dB	≤ 1.9 dB	1.20
450	≤ 8.9 dB	≤ 2.7 dB	0.83
900	≤ 12.8 dB	≤ 3.9 dB	0.58

Frequency (MHz)	Attenuation (per 100m)	Attenuation (per 100ft)	Power kW
1500	≤ 16.8 dB	≤ 5.1 dB	0.44
1800	≤ 18.6 dB	≤ 5.7 dB	0.40
2000	≤ 19.6 dB	≤ 6.0 dB	0.37
2500	≤ 22.2 dB	≤ 6.8 dB	0.33
5800	≤ 35.5 dB	≤ 10.8 dB	0.21

Certifications & Standards

RoHS 3 Compliant : Yes REACH Compliant : Yes

UKCA CPR Classification : Fca to BS EN 50575:2014+A1:2016

Publication Date: 30/01/2023

Revision Number: 2.0
Written by: GB
Authorised by: GB

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.

