



2 & 4 Core Pink Speaker Cable

Mechanical & Electrical Characteristics

| | | |
|-----------------------------------|------------------|----------------------------------|
| Construction: | Inner Conductor: | Plain Annealed Copper |
| | Dielectric: | LSZH Insulation |
| | Sheath: | LSZH |
| Conductor Diameter: | | From 1.50 to 2.50mm ² |
| Sheath Diameter: | | 2 Core 6.70 ± 0.30mm |
| | | 4 Core 7.80 ± 0.30mm |
| Storage/Operating Temperature: | | -15°C to +70°C |
| Minimum Installation Temperature: | | -5°C |
| Core Colour 2 Core: | | Red, White |
| Core Colours 4 Core: | | Red, White, Black, Green |
| Sheath Colours: | | Pink |

*Cable image and colours are for illustration purposes only and may vary.

Application

Speaker cable for audio connections between loudspeakers and audio amplifiers.

Specifications

CPR Class: E

Electrical Characteristics

DC Resistance Inner Conductor @ 20°C:

| | |
|---------------------|--------------------|
| 1.50mm ² | ≤ 13.3 Ω/km @ 20°C |
| 2.50mm ² | ≤ 7.98 Ω/km @ 20°C |

| | |
|--------------------|--------------------------|
| Capacitance: | Up to 68.9pF/m (nominal) |
| Inductance: | Up to 0.00126mH/m |
| Operating Voltage: | 50V |

