



MAP2RFM3USAT

4-input (FM, III+DAB, UHF, SAT) mast amplifier with 25dB gain and up to 116dBμV output level on UHF band, separate VHF/UHF amplification with independent gain adjustment (0-15dB) for each input and low noise figure.

- RED Compliant: each model perfectly complies the Radio Spectrum and the Electromagnetic Compatibility and Safety indicated in recent European directives.
- Zamak die-cast frame with metal covers for extremely high noise shielding (LTE Free).
- The protective shell (ABS) has a simplified slide and easy tilting opening for the amplification section, thus facilitating the installer's work during the cable connections and installation of the mast amplifier.
- Dip-switch for enable the remote power supply on UHF input or on V+U input, depending on the model.
- Power Supply status LED and mast strap up to 60mm

ITEM		MAP2RFM3USAT
Code		223716
Input no.		4 (passaggio DC e toni DiSEqC tra uscita e ingresso SAT)
Input band		FM, III+DAB, UHF, SAT
Output level	(dBμV	7) 112, 116
Gain	(dB)	22, 20, 25, -1
Gain adjustment	(dB)	15, 15, 15, -
Noise figure	(dB)	6, 6, 6, -

Data sheet



Current consumption (mA) 80@12Vdc o STB