



Televes reserves the right to modify the product

Pre-terminated optical fiber patch cord

SC/APC, Single-mode (SM), LSFH indoor

Single-mode (SM) optical-fiber patch cord pre-terminated with SC/APC connectors for the interconnection of optical equipment. The sheath being LSFH, it is recommended for indoor use. Supplied in individual bag with hanger.

Ref.232621	2m	
	Art.Nr	OSK2SCAPC
	EAN13	8424450187029
Ref.232623	0.5m	
	Art.Nr	OSK05SCAPC
	EAN13	8424450208700
Ref.232626	1m	
	Art.Nr	OSK1SCAPC
	EAN13	8424450239001

Main features

- ITU-T G.657A2 fiber type
- LSFH sheath, orange colour
- SC/APC connectors

Technical specifications

Fiber core type		ITU-T-G657A2
Fiber core diameter	μm	9
Fiber cladding diameter	μm	125
Coating buffer diameter	μm	250
Cable structure		Tight buffer
Plastic buffer diameter	μm	900
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Attenuation 1310nm	dB/km	< 0.4
Attenuation 1490nm	dB/km	< 0.4
Attenuation 1550nm	dB/km	< 0.3
Insertion losses in connector 1	dB	< 0.5
Insertion losses in connector 2	dB	< 0.5
Return losses in connector 1	dB	> 55
Return losses in connector 2	dB	> 55
Optical connector type 1		SC
Polishing type (Optical connector 1)		APC
Optical connector type 2		SC
Polishing type (Optical connector 2)		APC
Structure reinforcement element		Fibras de aramida
Minimum bending radius	mm	15
Operating temperature	°C	-20 ... 70