



*Televés reserves the right to modify the product*

## Overlight dCSS Optical Receiver: 2 dCSS/Legacy+Terr. outputs and 2 Terr. outputs + PSU (UK plug), SKY applications, FM/DAB/UHF/SAT

Complete optical Wideband satellite and terrestrial receiver and power supply unit with UK plug. The receiver captures the TV optical signal on a single fiber (1200...1600 nm) and restores the original terrestrial and satellite TV signals, providing 4 RF outputs: 2 dCSS/Legacy + Terr. outputs and 2 Terr. outputs.

Thanks to its optimized electronics and low losses, it allows to reduce the number of amplifiers required and simplifies deployment in the design of collective installations, preserving the signal quality throughout the process. Furthermore, it is fully indicated for use in GPON installations, and it perfectly adapts to SKY applications.

This device is part of the Overlight system, that distributes satellite and terrestrial signals to multiple users through a single optical fiber.

---

<b>Ref.</b>	237623
<b>EAN13</b>	8424450317440

---

## Other features

---

**Plug type** UK plug

---

## Packaging info

---

**Box** 1 pcs.

---

## Physical data

---

**Net weight** 530.00 g

**Gross weight** 560.00 g

---

**Width** 125.00 mm

**Height** 91.00 mm

---

**Depth** 30.00 mm

---

**Main product weight** 360.00 g

---

## Highlights

---

- Very compact in dimensions and weight
- Compatible with GPON deployments
- Supports SKY modes
- Low losses
- Optimized electronic behavior
- 100% European design, quality, and manufacturing
- SC/APC optical connector
- F-type RF connectors
- High-screening Zamak chassis
- Can be wall-mounted using screws

## Application example

---

