



SWI8532STPLUS

Cascadable 5-input multiswitches with active gain and separate adjustment in the TV and Satellite bands (high and low band with separate adjustments). **Coupled mechanics.**

| SWI8532STPLUS | | |
|----------------------------------|------|-------------|
| Code | | 271058 |
| Inputs | | 4 SAT, 1 TV |
| Taps | | 32 |
| SAT | | |
| Bandwidth | MHz | 950-2150 |
| Positive slope gain | dB | -24 |
| Gain adjustment | dB | 15 |
| Max output level (-35dBc 2 tone) | dBμV | 108 |
| Insertion loss | dB | -5 |
| SAT-SAT Isolation | dB | >45 |
| TV | | |
| Bandwidth | MHz | 85-862 |
| Positive slope gain | dB | -10/-4 |
| Gain adjustment | dB | 20 |
| Max output level (-35dBc 2 tone) | dBμV | 102 |
| Insertion loss | dB | -4 |
| Return path | | |

| | | |
|----------------------------------|------|------|
| Bandwidth | MHz | 5-65 |
| Gain | dB | -6 |
| Max output level (-35dBc 2 tone) | dBμV | 100 |
| Insertion loss | dB | -2 |

Features

| | | |
|-----------------------|-------|-----------------|
| Current consumption | mA, V | 440, 14 340, 18 |
| Dimensions | mm | 440x120x60 |
| Operating temperature | °C | -10÷+55 |