


SCD2-5816W

SCD2 (dCSS) Multiswitches



5-input cascadable SCD2 (dCSS) multiswitch with CAG; compatible also with **Wideband LNBS**; **8 output taps** with 16 frequencies each and **operating mode autodetection**, entirely fed by **DC-IN connector, VL line** or by the receivers. SKY Italian frequencies.

Technical Chars

- Series with **4 satellite inputs and 1 TV input, 5 pass-through outputs and 2, 4, 6 or 8 user extensions**, 4 SCR tuners and 12 dCSS SCD2 tuners simultaneously for each output.
- Compatible with both conventional LNB(**UX-QT LTE**) and **Wideband LNB (UX-WB LTE)** to distribute the **4 polarities of a satellite with only two cables**.
- **Passive TV** input to mix DTT and Satellite signals in distribution.
- **Automatic Gain Control (CAG)**: maintains an adequate output signal (85dBμV) even when input signal strength varies.
- **Autodetection of the operating mode** depending on the STB connected to the port; this allows switching from a Legacy STB to an SCR or SCD2 without any intervention on the system. The multiswitch automatically starts in **Legacy** mode and switches to **SCR or SCD2** mode as soon as it detects a DiSEqC command.
- Low handover loss.
- DC pass-through on all satellite ports for maximum compatibility with existing installations.
- **FVM Flexible Voltage Management** allows the multiswitch to be powered in different modes without the need for a dip switch.
- **Universal standard**: compatible both with **SCR/SCD** and **SCD2** frequencies used by SKY and Tivùsat in Italy, and with **dSCR UK** English standard.
- **Power supply not included PSU3001 or AMP2000** with DC insertion on F connector to power the LNB, headend amplifier (if any) and multiswitch when the decoder cannot support the load of the extension.

SCD2-5816W		
Code		271179
Inputs		4 SAT, 1 TV
Outputs		4 SAT, 1 TV
Taps		8 to serve up to 8 Legacy users, 32 SCR users or 128 SCD2 users (dCSS)
Consumption		
Tap	mA	PSU su DC-IN o VL: 85; PSU su HL o VH: 400
Power supply	V	12-18
Current consumption	mA	PSU on DC-IN or VL: 1250; HL, VH or HH pass

Taps		
SAT bandwidth	MHz	950-2150
TV tap loss	MHz	40-790
SCR Frequencies	MHz	1210, 1420, 1680, 2040 (standard EN50494) 985, 1050, 1115, 1275, 1340, 1485, 1550, 1615, 1745, 1810, 1875, 1840 (standard EN50607)
TV		
TV bandwidth	MHz	40-790
Gain (Passive)	dB	-18
Insertion loss	dB	-4.5
SAT		
Bandwidth	MHz	Quattro: 950-2150; Wideband 250-2400
AGC	dB μ V	60-90
Max Output level SAT	dBuV	Legacy: 78, SCR/SCD2 (dCSS): 85
Insertion loss	dB	-3.5
Return loss	dB	>10
Features		
Working temperature	$^{\circ}$ C	-10 \pm +55
Dimensions	mm	260x109x50
SAT-SAT Isolation	dB	>25
Dimensions and packaging		
Pcs		1
EAN code		8016978103591
Packaging dimensions	mm - LxWxH	276 x 116 x 58
Packaging weight	Kg	0.94