

## **SWI1308TS**

Cascadable 13-input multiswitches with dip switch to select active or passive TV gain.



CODE		287365
Inputs		12 SAT, 1 TV
Taps		8
SAT		
Bandwidth M	1Hz	950-2300
Max output level (-35dBc 2 tone) d	ΒμV	100
Insertion loss di	В	0.333333
SAT-SAT Isolation dl	В	>30
ти		
Bandwidth M	1Hz	Passive: 5-862 Active: 47-862
BandwidthMGain (Active)dl		Passive: 5-862 Active: 47-862 -2
	В	
Gain (Active) dl	B B	-2 -22
Gain (Active)dlGain (Passive)dl	Β Β ΒμV	-2 -22
Gain (Active)dfGain (Passive)dfMax output level (-35dBc 2 tone) df	Β Β ΒμV	-2 -22 Active: 95
Gain (Active)dfGain (Passive)dfMax output level (-35dBc 2 tone) dfInsertion lossdfReturn pathdf	B B BµV B	-2 -22 Active: 95
Gain (Active)dfGain (Passive)dfMax output level (-35dBc 2 tone) dfInsertion lossdfReturn pathdf	B B BµV B	-2 -22 Active: 95 0.800000







Current consumption	mA, ۱	Active TV: 160, 13 Passive TV entirely powered by the receiver
Max LNB current consumption	mA	Passive TV: 4000 Active TV: 3840
Features		
Dimensions	mm	120x310x40
Operating temperature	°C	-0.181818
Features Dimensions	mA mm	Passive TV: 4000 Active TV: 3840 120x310x40