


## GX-BP-8T-R01A

Galaxia headend



**GX-BP-8T-R01A digital multi-modulator** board is equipped with one RF coaxial output connector (F Female) and is able to create up to **8 DVB-T digital terrestrial multiplexes**. The modulator is the ideal and efficient transmodulation solution for distributing tuned programs from satellite or terrestrial modules inserted in the **GALAXIA** chassis or available in sharing on the same backplane, also those IPTV multicast input.

### Technical Chars

- 1x RF coaxial output (F Female)
- Up to 8x DVB-T RF output multiplexes
- “Hot-swappable” module
- **WEB interface based headend:** the module is managed through a friendly user HTML web interface to set every single parameter

GX-BP-8T-R01A		
Code		287638
Bandwidth	MHz	6/7/8
Modulazione di uscita		
Modulazione intervallo guardia		1/4, 1/8, 1/16, 1/32
Bandwidth	MHz	6/7/8
RF output		
Output frequency	dB	47-862
Max output level	dBuV	85-105
Modulazione intervallo guardia		1/4, 1/8, 1/16, 1/32
Carriers		2k, 8k
MER RF	dB	>42
General features		
Connectors		1x F-female (RF)
Power Consumption	W	27
Dimensions	mm	270x115x20
Working temperature	°C	-5 ÷ 50