

GX-4T2CI-BP-00

Galaxia headend



GX-4T2CI-BP-00 è un ricevitore digitale terrestre dotato di un connettore di ingresso coassiale RF (F femmina) e due slot Common Interface PCMCIA. Il modulo è in grado di sintonizzare fino a **quattro multiplex digitali terrestri DVB-T/T2**, deciptare i programmi codificati tramite le CAM e le Smart Card inserite nei rispettivi slot C.I. e condividere i contenuti tramite back panel dello chassis **GALAXIA**.

Technical Chars

- 1x RF coaxial input (F Female)
- Tuning of up to 4x **DVB-T/T2 multiplexes**
- 2x **PCMCIA Common Interface** slots
- **"Hot-swappable"** module
- **WEB interface based headend:** the module is managed through a friendly user HTML web interface to set every single parameter

GX-4T2CI-BP-00		
Code		287641
Bandwidth	MHz	6/7/8
Inputs		
Input no.		1 (4 Channels)
Front-end		
Input no.		4
Input band	MHz	47-862
Input level	dBuV	30-88
Demodulators		DVB-T: QPSK/16QAM/64QAM DVB-T2: QPSK/16QAM/64QAM/256QAM
FEC		DVB-T: 1/4, 1/8, 1/16, 1/32 DVB-T2: 1/4, 1/8, 1/16, 1/32, 1/128, 19/256, 19/128
Modulazione di uscita		
Bandwidth	MHz	6/7/8
General features		
Connectors		1x F-female (RF)
Power Consumption	W	8
Common interface		2 x PCMCIA
Dimensions	mm	270x115x20
Working temperature	°C	-5 ÷ 50