



## TSC 50 Fibre patch cord 50m SC

Art. Number 307016



### Fibre Optic patch cord

The **TSC xx patch cord** is a single mode cable terminated with SC/APC connector plugs at both ends. It is recommended for indoor installations in cable ducts and cabinets of fibre optic networks used for applications like:

- CATV distribution and DOSIS data transmission
- SAT-IF, DVB-T, DAB and FM distribution
- Other fibre optic communication systems

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702663070165

### OPTICAL CHARACTERISTICS

Optical Attenuation 1310/1550 | dB/km 0.3 dB/km  
Optical cabletype Single-mode  
Fibre type G.652.D

### CONSTRUCTION

Jacket - material LSZH  
Jacket - dimension | mm 3.0 mm

### CHARACTERISTICS

Wavelength | nm 1310...1550 nm

### RETURN LOSS

Return Loss | dB >60 dB

### OPERATIONAL

Temperature - operating | °C -40...+80 °C

### CONNECTORS

Connector Type Optical - SC/APC



## Technical Specifications

### MECHANICAL

Minimum bending radius   mm	50 mm
Cable length   m	50 m
Colour	Yellow
Packaging Height   m	0.000 m
Packaging Width   m	0.000 m
Packaging Depth   m	0.000 m
Packaging Volume   m <sup>3</sup>	0.000 m <sup>3</sup>
Net Weight   kg	1.000 kg
Tara Weight   kg	0.005 kg
Total Weight   kg	1.005 kg