

connecting the future



HTS 3DC - 3 way splitter

Article number: 347013

Product description:

HTS 3DC - 3 way splitter. Low insertion loss. All ports impedance 75 Ohm. High isolation. Class A shielding - ideal for your TV system.

Specifications

Archive	Y
ORDER INFORMATION	
EAN Number	5702663470132
SHIELDING	
Shielding efficiency VHF/UHF	> 110.0 dB
FREQUENCY	
Frequency range	5...1000 MHz
LOSS	
Insertion loss (in-out) 5-40 Mhz	< 5.2 dB
Insertion loss (in-out) 40-470 MHz	< 5.5 dB
Insertion loss (in-out) 470-860 MHz	< 6.0 dB
Insertion loss (in-out) 860-1000 MHz	< 6.5 dB

ISOLATION	
Isolation (tap-tap) 5-40 MHz	> 26.0 dB
Isolation (tap-tap) 40-470 MHz	> 28.0 dB
Isolation (tap-tap) 470-860 MHz	> 24.0 dB
Isolation (tap-tap) 860-1000 MHz	> 24.0 dB
RETURN LOSS	
Return loss (in-out) 5-40 MHz	> 24.0 / > 24.0 dB
Return loss (in-out) 40-470 MHz	> 22.0 / > 22.0 dB
Return loss (in-out) 470-860 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 860-1000 MHz	> 20.0 / > 20.0 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
DC Passthrough	Yes
CONNECTORS	
Number of outputs	3
MECHANICAL	
Product Height	50 mm
Product Width	74 mm
Product Depth	16 mm
Packaging Height	0,020 m
Packaging Width	0,050 m
Packaging Depth	0,070 m
Net Weight	0,045 kg
Tara Weight	0,006 kg
Total Weight	0,051 kg