

connecting the future



HTS 8DC - 8 way splitter

Article number: 347018

Product description:

HTS 8DC - 8 way splitter. Low insertion loss. All ports impedance 75 Ohm. High isolation. Class A shielding - ideal for your TV system.

Specifications

Archive	Y
ORDER INFORMATION	
EAN Number	5702663470187
SHIELDING	
Shielding efficiency VHF/UHF	> 110.0 dB
FREQUENCY	
Frequency range	5...1000 MHz
LOSS	
Insertion loss (in-out) 5-40 Mhz	< 10.2 dB
Insertion loss (in-out) 40-470 MHz	< 10.6 dB
Insertion loss (in-out) 470-860 MHz	< 11.5 dB
Insertion loss (in-out) 860-1000 MHz	< 12.0 dB

ISOLATION	
Isolation (tap-tap) 5-40 MHz	> 26.0 dB
Isolation (tap-tap) 40-470 MHz	> 28.0 dB
Isolation (tap-tap) 470-860 MHz	> 24.0 dB
Isolation (tap-tap) 860-1000 MHz	> 24.0 dB
RETURN LOSS	
Return loss (in-out) 5-40 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 40-470 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 470-860 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 860-1000 MHz	> 20.0 / > 20.0 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
DC Passthrough	Yes
CONNECTORS	
Number of outputs	8
MECHANICAL	
Product Height	60 mm
Product Width	117 mm
Product Depth	16 mm
Packaging Height	0,030 m
Packaging Width	0,030 m
Packaging Depth	0,100 m
Net Weight	0,128 kg
Tara Weight	0,012 kg
Total Weight	0,140 kg