

Data sheet

Taps and Splitters

HTS 16 - 16 way splitter

Item number 347916



Specifications

EAN Number	5702663479166
Frequency range	5-1000 MHz
Number of outputs	16
Insertion loss (in-out) 5-40 MHz	< 14.5 dB
Insertion loss (in-out) 40-470 MHz	< 14.5 dB
Insertion loss (in-out) 470-860 MHz	< 16.0 dB
Insertion loss (in-out) 860-1000 MHz	< 16.0 dB
Isolation (tap-tap) 5-40 MHz	> 26.0 dB
Isolation (tap-tap) 40-470 MHz	> 26.0 dB
Isolation (tap-tap) 470-860 MHz	> 23.0 dB
Isolation (tap-tap) 860-1000 MHz	> 23.0 dB
Return loss (in-out) 5-40 MHz	> 17.0 / > 17.0 dB
Return loss (in-out) 40-470 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 470-860 MHz	> 17.0 / > 17.0 dB
Return loss (in-out) 860-1000 MHz	> 17.0 / > 17.0 dB
Shielding efficiency VHF/UHF	> 110.0 dB
DC Passthrough	NO
Connector Type	F-female
Impedance	75 Ω
Certification	CE
Height (mm)	78 mm
Depth (mm)	44 mm
Width (mm)	242 mm
Weight (kg)	0,615 kg
Packaging Depth	0,240 m

Specifications

Packaging Height	0,050 m
Total Weight	0,300 kg
Packaging Width	0,080 m
Packaging Volume	0,001 m ³
Net Weight	0,300 kg
Tara Weight	0,000 kg