

connecting the future



LTE F 100/1 - PSU

Article number: 370111

Product description:

Power Unit with F Connectors

- F Connector
- Fully Screened
- Short Circuit and Thermal Fuse protected
- Power on LED
- UK plug

Specifications

ORDER INFORMATION	
EAN Number	5702663701113
CHARACTERISTICS	
Type	Power supply
FREQUENCY	
Input 1 - channels	2...60
Input 1 - frequency	5...790 MHz
LTE protection	@ 800Mhz
Band	VHF / UHF

GAIN	
Input 1 - gain	<2.0 dB
LOSS	
Rejection @ 821 MHz (LTE D6)	>18.0 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
AC Supply voltage	230Vac +/-10%, 3VA VAC
PSU output DC voltage	12 VDC
DC Current consumption	< 100 mA
LED indicator	Green
CONNECTORS	
Number of outputs	1
Number of inputs	1
MECHANICAL	
Product Depth	48 mm
Packaging Depth	0,088 m
Packaging Height	0,048 m
Total Weight	0,375 kg
Packaging Width	0,200 m
Net Weight	0,325 kg
Remarks	Screened Housing, gold plated connectors, UK plug only
Tara Weight	0,050 kg
Packaging Volume	0,001 m ³
Product Width	88 mm
Product Height	200 mm