

Part Number: 390150E-LSNH-BLU/RED

Description: WEB 18/22 Red Stripe 1pair 22awg +
1pair 18awg LSNH Blue with Red Stripe



Product Construction

Alternative to Lutron	:	GRX-CBL-346S
Data		
Conductor Material	:	Bare Copper
Conductor Stranding	:	22awg, 7/0.25mm
Insulation Material	:	Polyethylene (PE)
Number of Pairs	:	1
Core Colours	:	White, Violet
Drain Wire	:	Tinned Copper, 24awg
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%

Power

Conductor Material	:	Bare Copper
Conductor Stranding	:	18awg, 7/0.40mm
Insulation Material	:	Polyethylene (PE)
Number of Cores	:	2
Core Colours	:	Black, Red

Overall Construction

Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Blue + Red Stripe

Mechanical Characteristics

Overall Diameter	:	5.0mm ± 0.2mm
Temperature Range	Fixed	-20°C to +70°C
	Flexing	0°C to +60°C
Bend Radius	:	10 x Overall Diameter
Weight	:	45 kg/km

Electrical Characteristics

Conductor DC Resistance @ 20°C	: Data	≤ 55.4 Ω/km
	: Power	≤ 21.9 Ω/km
Capacitance, Data	Core to Core	82 pF/m ± 15
	Core to Screen	165 pF/m ± 25
Insulation Resistance @ 20°C	:	≥ 5000 M Ω*km
Voltage Rating	:	300/300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016



CEDIA®
MEMBER

Publication Date: 26/10/2022
Revision Number: 2.0
Written by: GB
Authorised by: GB