

Part Number: 441006E-WHT-01  
 Description: RG6 CCS 75ohm Coax PVC White



**Product Construction**

Conductor Material	:	Copper Clad Steel
Conductor Stranding	:	Solid, 1/1.02mm
Dielectric Material	:	Foam Polyethylene (FPE)
Dielectric Diameter	:	4.6mm ± 0.10
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	> 100%
Screening 2	:	Aluminium Wire Braid
Screening 2 Coverage	:	> 35% ± 3
Sheath Material	:	Polyvinyl Chloride (PVC)
Sheath Colour	:	White



**Mechanical Characteristics**

Overall Diameter	:	6.8mm ± 0.2mm
Temperature Range	Fixed	-15°C to +70°C
	Flexing	0°C to +60°C
Bend Radius	:	10 x Overall Diameter
Weight	:	41 kg/km

**Electrical Characteristics**

Inner Conductor DC Resistance	:	≤ 120 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 54 Ω /km @ 20°C
Characteristic Impedance	:	75 Ω ± 3
Nominal Capacitance	:	53 pF/m ± 3
Velocity of Propagation	:	82%

**Attenuation @20°C**

Frequency (MHz)	Attenuation (per 100m)	Frequency (MHz)	Attenuation (per 100m)
100	≤ 10.1 dB	1000	≤ 22.8 dB
200	≤ 11.5 dB	1350	≤ 25.2 dB
500	≤ 15.5 dB	1750	≤ 30.2 dB
800	≤ 18.8 dB	2150	≤ 32.5 dB

**Return Loss @ 20°C**

Frequency (MHz)	Return Loss
5MHz - 470MHz	≥ 20 dB
470MHz - 2150MHz	≥ 18 dB

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-1-2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

Publication Date: 22/01/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.