

Part Number: 480005E-LSNH-BLK

Description: RG213 /U 50ohm Coaxial Cable Low
 Smoke Non-Halogen (LSNH) Black



Product Construction

Conductor Material	:	Bare Copper
Conductor Stranding	:	Stranded, 7/0.75mm
Dielectric Material	:	Solid Polyethylene (SPE)
Dielectric Diameter	:	2.25mm ± 0.18
Screening 1	:	Bare Copper Wire Braid
Screening 1 Coverage	:	> 97% ± 3
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Black



Mechanical Characteristics

Overall Diameter	:	10.3mm ± 0.15mm
Temperature Range	Fixed	-15°C to +70°C
	Flexing	-5°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	165 kg/km

Electrical Characteristics

Inner Conductor DC Resistance	:	≤ 6.0 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 4.4 Ω/km @ 20°C
Impedance	:	50 Ω ± 3
Nominal Capacitance	:	100 pF/m ± 3
Velocity of Propagation	:	66%
Shielding Effectiveness 100-900MHz	:	> 57 dB

Attenuation @20°C

Frequency (MHz)	Attenuation (dB/100m)	Frequency (MHz)	Attenuation (dB/100m)	Frequency (MHz)	Attenuation (dB/100m)
5	≤ 1.2 dB	500	≤ 15.3 dB	1750	≤ 33.7 dB
10	≤ 1.8 dB	600	≤ 16.9 dB	2150	≤ 38.9 dB
50	≤ 4.3 dB	800	≤ 20.4 dB	2250	≤ 39.7 dB
100	≤ 6.4 dB	1000	≤ 23.2 dB	2500	≤ 42.7 dB
200	≤ 9.5 dB	1350	≤ 28.4 dB	2750	≤ 45.7 dB
400	≤ 13.7 dB	1500	≤ 30.4 dB	3000	≤ 48.9 dB

Return Loss @ 20°C

Frequency (MHz)	Return Loss
30MHz - 300MHz	≥ 31 dB
300MHz - 600MHz	≥ 28 dB
60MHz - 1000MHz	≥ 27 dB
1000MHz - 2000MHz	≥ 24 dB
2000MHz - 3000MHz	≥ 22 dB

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

Publication Date: 07/03/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.