

Part Number: 600005F-BLK

Description: WF125 75ohm Coax PE Black - CAI
Approved



Product Construction

Conductor Material	:	Plain Annealed Copper
Conductor Stranding	:	Solid, 1/1.25mm
Dielectric Material	:	Foam Polyethylene (FPE)
Dielectric Diameter	:	5.75mm $\pm$ 0.10
Screening 1	:	Overall Plain Copper Foil
Screening 1 Coverage	:	> 100%
Screening 2	:	Plain Copper Wire Braid
Screening 2 Coverage	:	> 60% $\pm$ 3
Sheath Material	:	Polyethylene (PE)
Sheath Colour	:	Black



Mechanical Characteristics

Overall Diameter	:	8.0mm $\pm$ 0.3mm
Temperature Range	Fixed	-15°C to +70°C
	Flexing	-5°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	70 kg/km

Electrical Characteristics

Inner Conductor DC Resistance	:	$\leq$ 15.0 Ω /km @ 20°C
Outer Conductor DC Resistance	:	$\leq$ 13.5 Ω /km @ 20°C
Characteristic Impedance	:	75 Ω $\pm$ 3
Nominal Capacitance	:	54 pF/m $\pm$ 3
Velocity of Propagation	:	82%

Attenuation @20°C

Frequency (MHz)	Attenuation (per 100m)	Frequency (MHz)	Attenuation (per 100m)
5	$\leq$ 1.5 dB	860	$\leq$ 15.5 dB
50	$\leq$ 3.5 dB	1000	$\leq$ 17.0 dB
100	$\leq$ 5.0 dB	1750	$\leq$ 22.0 dB
200	$\leq$ 7.5 dB	2150	$\leq$ 26.0 dB
460	$\leq$ 11.5 dB		

Return Loss @ 20°C

Frequency (MHz)	Return Loss
5MHz - 470MHz	$\geq$ 23 dB
470MHz - 862MHz	$\geq$ 20 dB
862MHz - 2150MHz	$\geq$ 18 dB

Certifications & Standards

CAI Certification	:	CAI 0142E
Screening Class	:	BS EN 50117
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Fca to BS EN 50575:2014+A1:2016

CEDIA[®]
MEMBER



Publication Date: 04/07/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.