



signature

For The True Audiophile

Signature by Episode 7 Series

If you're a true audiophile, opt for the 7 Series. A honeycomb fiberglass Nomex woofer and pure titanium tweeter offer the best in distributed audio or home theater sound.



Sound Science

Signature by Episode delivers superior audio through three scientific philosophies: low distortion, wide dispersion, and flat frequency response – providing unmatched audio accuracy for a fully-immersive lifelike experience.

Accurate Reproduction

Using flat frequency response, Signature by Episode delivers audio without frequency bias, producing sound true to what the artist intended and giving you the most accurate and lifelike experience possible.

Adaptable Listening

Signature by Episode delivers the same high-quality sound at both low and high volumes by using lighter, stiffer driver materials with greater excursion and tweeters that can play lower into the frequency band.

Low-Profile

Your speakers will blend in wherever they're placed thanks to our thin-bezel paintable grilles and affordable flush-mount brackets that provide a smooth, minimalistic finish.

Signature by Episode 7 Series

| | SIG-76-IC | SIG-78-IC | SIG-76-ICSURR | SIG-78-ICSURR | SIG-76-POINT | SIG-76-IW | SIG-78-IW | SIG-76-IWSURR | SIG-76-IWLCR |
|---|---|---|---|---|--|--|--|---|---|
| Placement | In-Ceiling | In-Ceiling | In-Ceiling | In-Ceiling | In-Ceiling | In-Wall | In-Wall | In-Wall | In-Wall |
| Type | Standard | Standard | Surround | Surround | Point | Standard | Standard | Surround | LCR |
| Connector Type | Gold plated push terminals | Gold plated push terminals | Gold plated push terminals | Gold plated push terminals | Gold plated push terminals | Gold plated push terminals | Gold plated push terminals | Gold plated push terminals | Gold plated push terminals |
| Frequency Response | 41 Hz - 20 kHz | 32 Hz - 20 kHz | 41 Hz - 20 kHz | 32 Hz - 20 kHz | 41 Hz - 20 kHz | 41 Hz - 20 kHz | 31 Hz - 20 kHz | 41 Hz - 20 kHz | 41 Hz - 20 kHz |
| Adjustments | Tweeter +2dB/0/-2dB, Woofer +2dB/0/-2dB | Tweeter +2dB/0/-2dB, Woofer +2dB/0/-2dB | Surround Mode Bi/Di, Tweeter +2dB/0/-2dB | Surround Mode Bi/Di, Tweeter +2dB/0/-2dB | Tweeter +2dB/0/-2dB, Woofer +2dB/0/-2dB | Tweeter +2dB/0/-2dB, Woofer +2dB/0/-2dB | Tweeter +2dB/0/-2dB, Woofer +2dB/0/-2dB | Surround Mode Bi/Di, Tweeter +2dB/0/-2dB | "Dialogue Enhancement On/Off, Tweeter +2dB/0/-2dB" |
| Crossover Frequency | 2.5 kHz | 2.2 kHz | 2.5 kHz | 2.2 kHz | 2.35 kHz | 2.6 kHz | 2.3 kHz | 2.6 kHz | 2.5 kHz |
| Nominal Impedance | 8 ohm | 8 ohm | 8 ohm | 8 ohm | 8 ohm | 8 ohm | 8 ohm | 8 ohm | 8 ohm |
| Power Peak | 140 Watts | 160 Watts | 140 Watts | 140 Watts | 140 Watts | 140 Watts | 160 Watts | 140 Watts | 140 Watts |
| Sensitivity | 90 dB | 91 dB | 90 dB | 91 dB | 90 dB | 90 dB | 91 dB | 90 dB | 89 dB |
| Tweeter | 3/4" | 1" | 3/4" | 1" | 3/4" | 1" | 1" | 3/4" | 3/4" |
| Woofer | 6" | 8" | 6" | 8" | 6" | 6" | 8" | 6" | 6" |
| Mounting | Mounting Depth: 4.8" Mounting Depth w/ Enclosure: 6.2" | Mounting Depth: 5.2" Mounting Depth w/ Enclosure: 6.6" | Mounting Depth: 4.8" Mounting Depth w/ Enclosure: 6.2" | Mounting Depth: 5.2" Mounting Depth w/ Enclosure: 6.6" | Mounting Depth: 5.2"/Mounting Depth w/ Enclosure: 6.6" | "Mounting Depth: 3.6" Mounting Depth w/ Enclosure: 3.8" | "Mounting Depth: 3.6" Mounting Depth w/ Enclosure: 3.8" | Mounting Depth: 3.7" Mounting Depth w/ Enclosure: 3.8" | Mounting Depth: 3.7" Mounting Depth w/ Enclosure: 3.8" |
| Dimensions (W x H x D) | Finished Dimension w/ Grill: 9.6" | Finished Dimension w/ Grill: 11" | Finished Dimension w/ Grill: 9.6" | Finished Dimension w/ Grill: 11" | Finished (Size with Grille): 11" | Finished Dimension w/ Grill: 8.9" x 13" | Finished Dimension w/ Grill: 10.3" x 15" | Finished Dimension w/ Grill: 8.9" x 13" | Finished Dimension w/ Grill: 8.9" x 15.7" |
| Cutout Dimension (Diameter for IC) (Height x Width for IW)* | 8.3" | 9.7" | 8.3" | 9.7" | 9.7" | 11.7" x 7.6" | 13.7" x 9" | 11.7" x 7.6" | 7.6" x 14.4" |
| Weight | 4.7 lb | 6.1 lb | 4.8 lb | 5.3 lb | 5.2 lb | 5.7 lb | 6.1 lb | 5.7 lb | 7.8 lbs |
| Dog ear clamping range | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate | 3/8" to double 1/2" substrate |
| Optimal Air Volume Behind Speaker | 15 ~ 20 Liters | 40 ~ 45 Liters | 15 ~ 20 Liters | 40 ~ 45 Liters | 15 ~ 20 Liters | 15 ~ 20 Liters | 35 ~ 40 Liters | 15 ~ 20 Liters | 35 ~ 40 Liters |
| Listening angle | 110 | 110 | 110 | 110 | 120 | 100 | 100 | 100 | 100 |



 signature