



## Nemesis DS Player T.0X 19" Rack Mounting

Digital Signage Player based on Nemesis Set-Top Box, designed for 19" Rack mounting. This high definition decoder supports both IPTV and Digital Signage, including a 16 GB microSD memory card for storing the multimedia content that has been scheduled to be played on the device through Arantia DS management tool. It includes support for both vertical and horizontal display orientation. It can work autonomously and it has a fall-back mechanism in case of any problem in the network access to the Arantia DS system so that the STB continues playing the scheduled content.

This device includes one year license for accessing Arantia DS system when it has been configured to work remotely against Televes cloud Digital Signage platform.

Its chassis includes a mounting plate for rack mounting.

<b>Ref.</b>	831815
<b>Logical ref.</b>	ADS-N19
<b>EAN13</b>	8424450222539

### Packaging info

<b>Box</b>	1 pcs.
------------	--------

### Physical data

<b>Net weight</b>	365.00 g
<b>Gross weight</b>	365.00 g

### Highlights

- Share commercial information and topics of interest with the customers
- Content management with the option to choose how and when to display it
- Versatile solution adapted to the establishment
- Broadcasting of relevant news, warnings and safety recommendations
- Entertainment content visualization in those places that require long waiting time
- MPEG2 and MPEG4 AVC / H264 platform
- High definition resolution up to 1080p60
- Advanced user interface navigation via embedded browser
- HDMI interface
- Dual USB 2.0 high-speed communication port
- TV Interactive interface (TVI) and IR extender
- Remote configuration and management
- Open-standards based software stack
- Modular software architecture ready for features and services development
- HTML5 web-browser with extended JavaScript API
- Ecodesigned STB with very low power consumption (~3 W)
- T.OX 19" rack compatible

## Main features

---

- MPEG2 and MPEG4 AVC / H264 platform
- High definition resolution up to 1080p60
- Advanced user interface navigation via embedded browser
- HDMI interface
- Dual USB 2.0 high-speed communication port
- TV Interactive interface (TVI) and IR extender
- Remote configuration and management
- Open-standards based software stack

- Modular software architecture ready for features and services development
- HTML5 web-browser with extended JavaScript API
- Ecodesigned STB with very low power consumption (~3W)
- T.0X 19" rack compatible