



6 Port 10/100Mbps Network Switch (4 Ports PoE / 2 Uplink Ports) 990.109

Power	
Power Adapter Voltage	Input : 110-240V/AC 50-60Hz
The maximum power supply machine	65W(52V 1.25A)
Network Connector	
Network Port	4*10/100Mbps POE port 2*10/100Mbps UP Link port
Transmission Distance	Extend switch is default OFF, state(1~4 port) : 100m Extend switch is ON, state:(1~4 port): 250m WAN1/2 port: 100m
Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	
Network Standard	IEEE802.3/10BASE-T Ethernet
	IEEE802.3u/100BASE-TX Ethernet
	IEEE802.3x Flow Control, IEEE802.3af, IEEE802.3at
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port
	100BASE-T : 148800pps/port
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
MAC address lis	1K
Backplane bandwidth	1.6Gbps
PoE Standard	IEEE 802.3af, IEEE 802.3at
Power Over Ethernet	
PoE Power Supply Type	End-Span(1/2+,3/6-)
PoE Power Consumption	af,at Adaptive (every port)
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
ESD	
/	Air discharge: 8KV Contact discharge: 4KV