



10 Port 10/100Mbps Network Switch (8 Ports PoE / 2 Gigabit Uplink Ports) 990.219

Power

Power Adapter Voltage Input: 110-240V/AC 50-60Hz

The maximum power supply machine 120W(52V 2.3A)

Network Connector

Network Port 8*10/100mbps POE port
2*100/1000mbps UP Link port

Transmission Distance Extend switch is default OFF, state(1~8 port): 100m
Extend switch is ON, state:(1~8 port): 250m
WAN1/2 port: 100m

Transmission Medium Cat5/5e/6 standard network cable

Network Switch

Network Standard IEEE802.3/10BASE-T Ethernet
IEEE802.3u/100BASE-TX Ethernet
IEEE802.3x Flow Control, IEEE802.3af, IEEE802.3at

Forwarding Mode Store and forward

Forwarding Rate 10BASE-T:14880PPS/port
100BASE-T : 148800pps/port

Network Medium 10/100BASE-TX:5 class and above non shielded twisted pair

MAC address 2K

Backplane bandwidth 10Gbps

PoE Standard IEEE 802.3af, IEEE 802.3at

Power Over Ethernet

PoE Power Supply Type End-Span(1/2+,3/6-)

PoE Power Consumption af,at Adaptive (every port)

Port Function Power priority mechanism, fast and forward, MAC automatic learning and aging
IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode

ESD

/

Air discharge: 8KV
Contact discharge: 4KV