AMPLIFI

DATASHEET



AmpliFi™ Instant Wi-Fi

Models: AFi-INS, AFi-INS-R

Turbocharged 802.11ac Wi-Fi

Complete Home Wi-Fi System


Perfected User Experience



AMPLIFI

Overview

AmpliFi Routers and MeshPoints are designed to work in combination to eliminate any dead spots in your home. They utilize mesh technology to provide powerful wireless performance in an innovative and simple design.






Router





MeshPoint





INSTANT WI-FI SYSTEM

Model: AFi-INS

The AmpliFi Instant Wi-Fi System includes an AmpliFi Instant Router and a wireless MeshPoint. It combines instant deployment flexibility with maximum Wi-Fi coverage for your home.



INSTANT ROUTER

Model: AFi-INS-R

The AmpliFi Instant Router takes advantage of AmpliFi's powerful performance and software features. Optionally, you can connect additional AmpliFi Mesh Routers or AmpliFi MeshPoints to expand range coverage.

Download on the App Store





android app on Google Play

Up and Running in Minutes!

The intuitive AmpliFi app allows instant setup, configuration, powerful reporting metrics, parental controls, remote access, and easy guest access. The mobile app is available for download on Android and iOS smartphones.

Router Specifications

| Dimensions | 99.5 x 97.8 x 33.05 mm (3.92 x 3.85 x 1.30") |
|------------------------|------------------------------------------------------------------------------|
| Weight | 215 g (7.58 oz) |
| Max. TX Power | 22 dBm |
| MIMO | 2.4 GHz: 2x2, 5 GHz: 2x2 |
| Speeds | 2.4 GHz: 300 Mbps, 5 GHz: 867 Mbps |
| Networking Interface | Wi-Fi/Gigabit Ethernet (1) WAN, (1) LAN |
| Max. Power Consumption | 9W |
| ESD/EMP Protection | ± 24kV Air/Contact |
| Buttons | Reset |
| Antennas | (1) Dual-Band Antenna, Single-Polarity |
| Display | 30.73 mm (1.21") diagonal, 160 x 64, 142 ppi, Capacitive Touch, Grayscale |
| Wi-Fi Standards | 802.11ac |
| Power Save | Supported |
| Wireless Security | WPA2-PSK AES/TKIP |
| Operating Temperature | 14 to 131° F (-10 to 55° C) |
| Operating Humidity | 5 to 95% Noncondensing |
| Certifications | FCC / CE / IC |

Supported Data Rates

| 802.11ac | 13 Mbps to 866.7 Mbps (MCS0 - MCS9, VHT 20/40/80) |
|----------|---------------------------------------------------|
| 802.11n | 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40) |
| 802.11a | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |
| 802.11b | 1, 2, 5.5, 11 Mbps |
| 802.11g | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |



MeshPoint Specifications

| Dimensions | 99.5 x 97.8 x 33.05 mm (3.92 x 3.85 x 1.30") |
|------------------------|----------------------------------------------|
| Weight | 215 g (7.58 oz) |
| Max. TX Power | 22 dBm |
| MIMO | 2.4 GHz: 2x2, 5 GHz: 2x2 |
| Speeds | 2.4 GHz: 300 Mbps, 5 GHz: 867 Mbps |
| Networking Interface | Wi-Fi/Gigabit Ethernet (1) LAN |
| Max. Power Consumption | 9W |
| ESD/EMP Protection | ± 24kV Air/Contact |
| Buttons | Reset |
| Antennas | (1) Dual-Band Antenna, Single-Polarity |
| Wi-Fi Standards | 802.11ac |
| Power Save | Supported |
| Wireless Security | WPA2-PSK AES/TKIP |
| Operating Temperature | 14 to 131° F (-10 to 55° C) |
| Operating Humidity | 5 to 95% Noncondensing |
| Certifications | FCC / CE / IC |

Supported Data Rates

| 802.11ac | 13 Mbps to 866.7 Mbps (MCS0 - MCS9, VHT 20/40/80) |
|----------|---------------------------------------------------|
| 802.11n | 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40) |
| 802.11a | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |
| 802.11b | 1, 2, 5.5, 11 Mbps |
| 802.11g | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |





Guest Access Simplified

AmpliFi utilizes an open time window concept to allow instant guest access without the security compromise and inconvenience of password sharing.



24/7 Live Global Chat Support

24/7 Live Global Chat Support within the AmpliFi app and also online at help.amplifi.com

