

900Mbps Project Outdoor CPE



Qualcomm Chipset



Open WRT OS



Wifi Transfer Tool



Security Monitoring



Outdoor Wifi Cover



Wifi Base Station



Beam PRO V2

CF-E313ACV2 Technical Specification	
Hardware Specifications	Chipset: Qualcomm QCA9563+QCA8337+QCA98866 ; RAM: DDR 128MB; Flash: 16MB; PA: SKY85735-1
Antenna	2* 14dBi Antenna
Wireless Standard	IEEE802.11a/an/ac
RF Parameters	Output Power (Max): 200mW (23dBm); Receiving Sensitivity (Max): -96dBm; Working Frequency: 5.180GHz-5.825GHz
Modulation Mode	DSSS: DBPSK@1Mbps, DQPSK@2Mbps, CCK@5.5/11Mbps; OFDM: BPSK@6/9Mbps, QPSK@12/18Mbps, 16-QAM@24Mbps, 64-QAM@48/54Mbps, 256-QAM@173/400/867Mbps; MIMO-OFDM: MCS 0-15
Transmission Rate	5.8GHz: 867Mbps
Physical Ports	1* 10/100/1000Mbps WAN RJ45 Ethernet Port; 1* 10/100/1000Mbps LAN RJ45 Ethernet Port; 1* RESET Button 1* POE Switch
Indicator	8* Indicators: Power/WAN/LAN/WiFi/Level/Signal Strength (1-4)
Power Supply	Power Supply: 802.3af/at POE Power Supply(0-100m); Power Adapter: 48V 0.32A POE Power Adapter(Configured)
Power Consumption	<8W
IP Index	2KV Lightning Protection IP65
MTBF	>250000H
Installation Way	Wall-mounted/Pole-mounted
Case	Plastic Case (Imported ABS Material)
Physical Features	Size: 262x80x53mm
Working Environment	Working Temperature: -10°C~55°C; Storage Temperature: -50°C~75°C; Working Humidity: 10%~90%RH Non-condensing; Storage Humidity: 5%~90%RH Non-condensing



Antiference®

Technology...since 1937



www.antiference.co.uk



sales@antiference.co.uk



01675 465487