KU Band Quattro LNB

BLASAT-LNB-QUATTRO-H High Gain Version





KU Band Quattro LNB

Designed for seamless residential satellite TV reception, the Quattro LNB combines affordability with high-performance engineering. Ideal for households seeking reliable signal clarity, this LNB ensures stable connectivity even in diverse weather conditions. With its user-friendly design and energy-efficient 150mA operation, the Quattro is your gateway to uninterrupted entertainment and dependable satellite communication.

- Ultra-Low Noise Figure (0.3dB) for interference-free signal quality
- Optimised Conversion Gain (>65dB) ideal for smaller dish installs.
- Dual Polarisation Flexibility to switch effortlessly between Vertical (11.5-14V) and Horizontal (16-19V) polarisations
- Robust Build with rain cover for F connectors
- Plug & Play Compatibility

Input Frequency	Low Band: 10.70-11.70Ghz High Band: 11.70-12.75Ghz
Output Frequency	Low Band: 950-1950MHz High Band: 1100-2150MHz
LO Frequency	Low Band: 9.75 GHz ±1MHz High Band: 10.60 GHz ±1MHz
LO Stability	±1 MHz (-40°C to +70°C)
Gain	≥65 dB ±3dB
Noise Figure	0.3dB
Operating Temperature	-40°C to +70°C