

# CF Clear Flow®

## Air 3 WiFi Access Point • 2.4GHz

### SPECIFICATION

<b>Product:</b>	<b>AIR3 2.4GHz 300Mbps</b>
<b>Product No</b>	<b>CF-E325N</b>
Wireless Standard	IEEE802.11b/g/n
Antenna	Internal 2x3dBi
Max Output Power	500mW 27dBm
Receiving Sensitivity	-96dBm
Frequency	802.11b/g/n 2.4-2.4835GHz
Modulation Mode:	
DSSS:	DQPSK@2Mbps, CCK@5.511Mbps
OFDM:	BPPSK@6/9Mbps, QPSK@12/18Mbps
	16-QAM@24Mbps,
	64-QAM@48/54Mbps
MIMO-OFDM:	MCS 0-15
Transmission	11b: 1.2, 5.5,11Mbps
	11g: 6,9,12,18,24,36,48,54Mbps
	11n:MCS0-MCS15 20 & 40MHz Analog
	20MHz 144.4Mbps, 40MHz 300Mbps
Power	48V 0.32A
Power Consumption	<8W
Size	200x200x18mm 0.31kg



2.4GHz Single band ceiling/wall mount WiFi access point for creating or expanding a wireless network. Simple on-board programming software accessible via smart device or laptop. Supplied with 48V PoE power injector.



WiFi CONNECTION



2.4GHz 300Mbps



WiFi DISTRIBUTION CONNECTION



ETHERNET CONNECTION



OPEN WRT OS



NETWORK OPTIMISED



DEVICE COMPATIBLE



CEILING MOUNTED



REQUIRES POWER



POWER ON INDICATOR



BOX CARTON

SCAN FOR VIDEO



SCAN FOR INFO



### SPECIFICATION

<b>Product:</b>	<b>AIR13 1300Mbps 11AC Dual Band</b>
<b>Product No:</b>	<b>CF-E375AC</b>
Wireless Standard	2.4 GHz 450Mbps, 5GHz 867Mbps
Antenna	Internal 3dBi
Max Output Power	500mW 27dBm
Receiving Sensitivity	-96dBm
Frequency	802.11a/n/a 5.18 - 5.825GHz
	802.11b/g/n 2.412 - 2.4835GHz
Modulation Mode:	
DSSS:	DBPSK@12Mbps, DQPSK@2Mbps,
	CCK@5.511Mbps
OFDM:	BPPSK@6/9Mbps, QPSK@12/18Mbps
	16-QAM@24Mbps, 64-QAM@48/54Mbps
MIMO-OFDM 11n:	MCS 0-23
MIMO-OFDM 11ac:	MCS 0-29
Transmission	11b: DSS CCK@5.5/11ps,
	DQPSK@2Mbps,
	DBPSK@1Mbps,
	11a/g OFDM 16-QAM@24Mbps,
	64-QAM@48/54Mbps, QPSK@12/18Mbps,
	BPSK@6/9Mbps,
	11n MIMO-OFDM: BPSK, QPSK, 16&64 QAM,
	11ac MIMO-OFDM: BPSK, QPSK, 16,64&256 QAM
Ports	1x10/100/1000Mbps WAN RJ45 Ethernet
	1x10/100/1000Mbps LAN RJ45 Ethernet
	1xReset, WPS button
Power	48V 0.5A
Power Consumption	<13W
Size	220x220x35mm 0.37kg

# CF Clear Flow®

## Air 13 WiFi Access Point • 2.4 & 5.8GHz



A dual band 2.4 & 5.8GHz ceiling/wall mount WiFi access point for advanced wireless networks. Maximum data speeds and increased users with simple programming software, Gb Ethernet port for super-fast broadband services.



WiFi CONNECTION



DUAL BAND GIGABIT



WiFi DISTRIBUTION CONNECTION



ETHERNET CONNECTION



OPEN WRT OS



NETWORK OPTIMISED



DEVICE COMPATIBLE



CEILING MOUNTED



REQUIRES POWER



BOX CARTON

SCAN FOR INFO

