

SPECIFICATION

| Product Range: | CF-POE4 | CF-POE8 |
|------------------------|---------------------------------|-----------------------|
| RJ45 Interface | 6*10/100/1000Mbps | 10*10/100/1000Mbps |
| PoE Ports | 1 - 4 | 1 - 8 |
| PoE Total | 65W | 120W |
| Power Supply | 72W | 125W |
| RJ45 PoE Power Supply | Mode A Anode 1/2, Cathode 3/6 | |
| PoE Power Output | 32W | 32W |
| Wireless Standard | IEEE802.3 af/at | |
| Network Media | 10BASE-T, UTP cat 5, 5e ≤100m | |
| | 100BASE-TX, UTP cat 5, 5e ≤100m | |
| | 1000BASE-T, UTP cat 5, 5e ≤100m | |
| MAC address table | 2K Auto study/updates | 8K Auto study/updates |
| Transfer Mode | Store & Forward | |
| Jumbo Frame | 9216 Bytes | 9216 Bytes |
| Packet Buffer | 1.5M bit | 2M bit |
| Packet Forwarding Rate | 8.9Mpps | 13.4Mpps |
| Bandwidth | 12Gbps | 20Gbps |
| Fan | Fanless | 1xFan |
| Power Supply | DC 54.5V/1.32A | AC 100-240V 50/60Hz |
| Size | 168x93x32mm | 220x150x44mm |

CF Clear Flow®

Clear Switch Ethernet Switch • 6 or 10 Port



Self-adaptive 48V PoE Ethernet switches for use with Clear Flow wireless networks. These unmanaged switches are ideal for delivering data and power to a Clear Flow system. Includes 4 or 8 ports PoE plus 2 additional uplink/downlink ports to connect to a larger switch or Clear Flow controller.



NETWORK DISTRIBUTION



GIGABIT



48V PoE 802.3af/at



ETHERNET CONNECTION



NETWORK OPTIMISED



CCTV COMPATIBLE



REQUIRES POWER



POWER ON INDICATOR



BOX CARTON

SCAN FOR INFO



SPECIFICATION

| Product: | CF-POE4/100 |
|------------------------|---------------------------------|
| RJ45 Interface | 6*10/100Mbps |
| PoE Ports | 1 - 4 |
| PoE Total | 60W |
| Power Supply | 65W |
| RJ45 PoE Power Supply | Mode A Anode 1/2, Cathode 3/6 |
| PoE Power Output | 32W |
| Wireless Standard | IEEE802.3 af/at |
| Network Media | 10BASE-T, UTP cat 5, 5e ≤100m |
| | 100BASE-TX, UTP cat 5, 5e ≤100m |
| MAC address table | 1K Auto study/updates |
| Transfer Mode | Store & Forward |
| Jumbo Frame | 1536 Bytes |
| Packet Buffer | 448K bit |
| Packet Forwarding Rate | 0.89Mpps |
| Bandwidth | 1.2Gbps |
| Fan | Fanless |
| Power Supply | AC 100-240V 50/60Hz |
| Size | 140x76.7x28mm |

CF Clear Flow®

Clear Switch Ethernet Switch • 6 Port



Self-adaptive 4 port PoE switch for use with a Clear Flow wireless network. Featuring 10/100 data speeds and 2 additional uplink/downlink ports, the CF-POE4/100 is ideal for use with the AIR3, BEAM2/5 & WAPU/T/D devices.



NETWORK DISTRIBUTION



48V PoE 802.3af/at



ETHERNET CONNECTION



NETWORK OPTIMISED



CCTV COMPATIBLE



REQUIRES POWER



POWER ON INDICATOR



BOX CARTON

SCAN FOR INFO

