



Pre-insulated PVC ring terminals.

Key features.

- Manufactured from oxygen-free high conductivity copper
- Electro-tin plated for excellent conductivity and resistance to corrosion

Specification.

Material:
Electro-tin plated copper

Insulation:
Polyvinyl chloride (PVC)

Approvals:
UL Approved E211389, RoHS compliant

Max. temperature:
75°C (PVC)

Max. voltage:
600V

Max. electrical rating:
■ Red - 19 AMP
■ Blue - 27 AMP
■ Yellow - 48 AMP

Flammability:
UL94 V-0



Wire Ø mm ²	Part no.	Stud size D2 mm	B	L	F	E	D	D1	Pack quantity
0.5 - 1.5 Red	CIR1-2	2.2	6.6	19.6	6.3	10.0	4.1	1.7	100
	CIR1-3	3.2	5.5	16.7	4.0	10.0	4.1	1.7	100
	CIR1-3.5	3.7	5.5	16.7	4.0	10.0	4.1	1.7	100
	CIR1-4	4.3	8.0	21.0	7.0	10.0	4.1	1.7	100
	CIR1-5	5.3	8.0	21.0	7.0	10.0	4.1	1.7	100
	CIR1-6	6.5	11.6	26.8	11.1	10.0	4.1	1.7	100
	CIR1-8	8.4	11.6	26.8	11.1	10.0	4.1	1.7	100
	CIR1-10	10.5	13.6	30.7	13.9	10.0	4.1	1.7	100
CIR1-12	13.0	19.2	35.6	16.0	10.0	4.1	1.7	100	
1.5 - 2.5 Blue	CIR2-3	3.2	6.4	17.5	4.3	10.0	4.5	2.3	100
	CIR2-3.5	3.7	6.4	17.5	4.3	10.0	4.5	2.3	100
	CIR2-4	4.3	8.5	22.0	7.8	10.0	4.5	2.3	100
	CIR2-5	5.3	9.5	22.0	7.3	10.0	4.5	2.3	100
	CIR2-6	6.5	12.0	27.0	11.0	10.0	4.5	2.3	100
	CIR2-8	8.4	12.0	27.0	11.0	10.0	4.5	2.3	100
	CIR2-10	10.5	13.6	30.7	13.9	10.0	4.5	2.3	100
	CIR2-12	13.0	19.2	35.6	16.0	10.0	4.5	2.3	50
4 - 6 Yellow	CIR3-3.5	3.7	9.5	25.5	8.3	12.5	6.5	3.4	50
	CIR3-4	4.3	9.5	25.5	8.3	12.5	6.5	3.4	50
	CIR3-5	5.3	9.5	25.5	8.3	12.5	6.5	3.4	50
	CIR3-6	6.5	12.0	29.0	10.5	12.5	6.5	3.4	50
	CIR3-8	8.4	15.0	33.7	13.7	12.5	6.5	3.4	50
	CIR3-10	10.5	15.0	33.7	13.7	12.5	6.5	3.4	50
	CIR3-12	13.0	19.2	38.1	16.0	12.5	6.5	3.4	50

01582 606033 | sales@cablecraft.co.uk | cablecraft.co.uk

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297

