

	HD TAB 9 <i>Plus</i>	HD TAB 900 <i>Plus</i>	TAB 7 <i>Ultra</i>	HD TAB 5 <i>Ultra</i>	HD TAB 5 <i>Lite</i>	HD TAB 5 <i>Sat</i>
			 <i>NEW</i>			
FREQ. RANGE	4 - 2450 MHz	5 - 2610 MHz	5 - 2610 MHz	30 - 2700 MHz	30 - 2700 MHz	700 - 2700 MHz
LEVEL RANGE	28 - 130 dBµV	28 - 130 dBµV	28 - 130 dBµV	35 - 115 dBµV	35 - 115 dBµV	35 - 115 dBµV
STANDARD DVB-T/S/S2/C	•	•	•	•	•	S - S2
STANDARD DVB-T2/T2 LITE	•	•	•	•	•	—
STANDARD DVB-S2 MULTISTREAM	•	•	—	—	—	—
WIDE BAND IN	—	•	•	—	—	—
SAT EXTENSION up to 2.610 MHz	opt.	•	•	—	—	—
DAB & DAB+	opt.	opt.	opt.	—	—	—
CAM C.I.	•	—	—	—	—	—
LTE ANALYSIS	•	•	—	•	•	—
OPTICAL INPUT	•	•	opt.	opt.	—	opt.
H265 HEVC	opt.	opt.	opt.	opt.	—	opt.
SAT EXPERT	•	•	•	•	•	•
TS ANALYZER ETR 101 290	•	—	—	—	—	—
TS RECORDER	opt.	opt.	opt.	—	—	—
MER VS CARRIER	•	•	•	•	•	—
MER	•	•	•	•	•	•
CONSTELLATION	•	•	•	•	•	•
DISEqC - dCSS - SCR	•	•	•	•	•	•
REFLECTOMETER	•	•	•	opt.	opt.	—
MINISPECTRUM	•	—	—	—	—	—
ECHOES ANALYSIS	•	•	•	•	•	—
ANALOG TV	MEAS & PICT	MEAS & PICT	MEAS (PICT opt.)	MEAS only	MEAS only	—
Wi-Fi	—	opt.	opt.	opt.	—	opt.
GPS	opt.	—	—	—	—	—
NOISE MARGIN GRAPH	•	•	•	•	•	•
IPTV	opt.	opt.	opt.	—	—	—
ASI IN-OUT	•	—	—	—	—	—
LAN	•	•	•	—	—	—
REMOTE MONITORING	•	•	•	—	—	—
DRIVE TEST	opt.	—	—	—	—	—
DOLBY AC3DD +	opt.	opt.	opt.	opt.	opt.	opt.
VIDEO IN RCA (CVBS)	•	•	•	•	•	—
HDMI OUT	•	•	•	—	—	—
USB	A + B	A + B	A + B	B	B	B
TFT	9"	9"	7" High Brightness	5"	5"	5"
TOUCH SCREEN DISPLAY	•	•	•	•	•	•
WEIGHT & DIMENSIONS	2,6 Kg / 29,0 x 17,0 x 5,5 cm	1,8 Kg / 15,5 x 27,0 x 4,0 cm	1,8 Kg / 27,0 x 15,5 x 4,0 cm	1,4 Kg / 13,0 x 25,5 x 4,0 cm	1,4 Kg / 13,0 x 25,5 x 4,0 cm	1,4 Kg / 13,0 x 25,5 x 4,0 cm
BATTERY CAPACITY	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours
BAG	RUGGED BAG	RUGGED BAG	RUGGED BAG	EASY BAG	EASY BAG	EASY BAG
DOCSIS	DOWN STREAM	DOWN STREAM	DOWN STREAM	DOWN STREAM	—	—