

# 75 SERIES Distribution Amplifiers · 1 & 2 Output



## SPECIFICATION

Product Range:	DA110	DA120
Inputs	1	1
Outputs	1	2
Frequency Range	470-694MHz	
Gain	15dB	12dB
Noise Max	4dB	4dB
Max Output	78dB	78dB
Line Power	-	-
Mains Power	230V AC ± 10% 50Hz	
Fitted Mains Plug	BS1363 3A rating	

The 75 Series range of indoor amplifiers for the distribution of UHF signals. Supplied with F-type connections for professional installations.



# 75 SERIES Distribution Amplifiers · 4, 6 & 8 Output



## SPECIFICATION

Product Range:	DA240LPA	DA261LPA	DA281LPA
Inputs	2	2	2
Outputs	4	6+1	8+1
Frequency Range	85-240/470-694MHz		
Gain	10dB	8dB	8dB
Noise Max	4dB	4dB	4dB
Max Output	78dB	78dB	78dB
Line Power	12v50mA	12v50mA	12v50mA
Mains Power	230V AC ± 10% 50Hz		
Fitted Mains Plug	BS1363 3A rating		

The 75 Series range of indoor amplifiers for distribution of UHF & VHF signals. The 4, 6 & 8 outputs have the added ability to power a masthead amplifier through the UHF input for pre-amplification convenience.

