

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Unifix GP HM Silicone

Revision: 15/07/2014

Page 1 from 3

Reference nr DOP: 230853

Unique identification code of the product type:

Unifix GP HM Silicone

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.

Sealant used for sealing glazing applications.

Sealants used for sanitary applications.

Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F – EXT-INT

EN 15651-2:2012: Type G

EN 15651-3:2012: Type S: CLASS S1

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3

System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

**Hexstone Limited t/as Unifix
Opal Way, Stone,
Staffordshire ST15 0SW
Factory 513**

The notified body:

GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Unifix GP HM Silicone

Revision: 15/07/2014

Page 2 from 3

Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	NPD	EN 15651-1: 2012 EN 15651-2: 2012 EN 15651-3: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3mm	
Loss of volume	NPD	
Elastic recovery	≥ 40%	
Adhesion/cohesion at maintained extension after water immersion	NF	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Elongation at break	≥ 25%	
Tensile properties at break after water immersion	≥ 25%	
Microbiological growth	0	
Durability	Pass	

Conditioning:

Method A

Substrate:

Aluminium

Mortar

Glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

John Barker Purchasing Director Unifix

Signature:



Date:

15/7/2014

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 15/07/2014

Page 3 from 3



NB 0074

Hexstone Limited

14

Reference nr DOP: 230853

EN 15651-1: 2012

EN 15651-2: 2012

EN 15651-3: 2012

Sealant for facade for interior and exterior application.

Sealant used for sealing glazing applications.

Sealants used for sanitary applications.

Unifix GP HM Silicone

EN 15651-1:2012: Type F – EXT-INT

EN 15651-2:2012: Type G

EN 15651-3:2012: Type S: CLASS S1

Conditioning:

Method A

Substrate:

Aluminium

Mortar

Glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	NPD	EN 15651-1: 2012 EN 15651-2: 2012 EN 15651-3: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3mm	
Loss of volume	NPD	
Elastic Recovery	≥ 40%	
Adhesion/cohesion at maintained extension after water immersion	NF	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Elongation at break	≥ 25%	
Tensile properties at break after water immersion	≥ 25%	
Microbiological growth	0	
Durability	Pass	