

## Digital Modulator • 4 HDMI Input



Wall mount 4 input HDMI to DVB-T modulator for distribution of multiple HDMI devices over an RF coax cable network. Programmed via Windows based USB software, ideal for commercial or domestic applications.

### SPECIFICATION

Product:	DMHD04C
Video Inputs:	HDMI
Resolution Modes:	720p - 1080p
Compression:	H.264 - bitrate 5-15Mb/s
Audio Inputs:	HDMI
Sample Rate:	HDMI (35kHz/44.1kHz/48kHz)
Compression:	AAC-LC or MPEG1-L2 bitrate 128-384 kb/s
	DVB Processing Table Insert: PAT, PMT, SDT, NIT, EIT
Configuration:	Channel/network name, SID audio/video PID's
DVB-T Output 3 channels:	170-230MHz + 470-862MHz > 95dBµV
Constellation FEC:	QPSK/16QAM/64QAM-1/2, 2/3, 3/4, 5/6, 7/8
Guard Interval:	1/4, 1/8, 1/16, 1/32
Mode MER:	2k/8k - 31dB
DVB-C Output 3 channels:	50-862Mhz/95dBµV
Constellation Symbol Rate:	16,32,64,128,256,QAM (EN300 429) 4,00 - 9,96Mps
Power DC:	+5v 15w
DMHD04C	Wall mounting 200x135x67mmDM



## Digital Modulator • 4 HDMI Input



Rack/shelf mountable 4 input HDMI to DVB-T modulator for distribution of up to 4 HDMI sources over coax cable network. Resolutions up to 1080p, with programmable Windows software, ideal for commercial/domestic use.

### SPECIFICATION

Product:	DMHD04D
Video Inputs:	HDMI
Resolution Modes:	720p - 1080p
Compression:	H.264 - bitrate 5-15Mb/s
Audio Inputs:	HDMI
Sample Rate:	HDMI (35kHz/44.1kHz/48kHz)
Compression:	AAC-LC or MPEG1-L2 bitrate 128-384 kb/s
	DVB Processing Table Insert: PAT, PMT, SDT, NIT, EIT
Configuration:	Channel/network name, SID audio/video PID's
DVB-T Output 3 channels:	170-230MHz + 470-862MHz > 95dBµV
Constellation FEC:	QPSK/16QAM/64QAM-1/2, 2/3, 3/4, 5/6, 7/8
Guard Interval:	1/4, 1/8, 1/16, 1/32
Mode MER:	2k/8k - 31dB
DVB-C Output 3 channels:	50-862Mhz/95dBµV
Constellation Symbol Rate:	16,32,64,128,256,QAM (EN300 429) 4,00 - 9,96Mps
Power DC:	+5v 15w
DMHD04D	Shelf/19" Rack mount 250x200x38mm

