

MAGNETIC LOCK

(H)

IP66 external range of maglocks and brackets from a market leader in access control



EXML1200-GATE & EXML1200-GATE-M

FEATURES

EXML1200-GATE & EXML1200-GATE-M

(H)

- · External magnet IP66
- Weatherproof
- · Dual voltage 12V/24V
- · Side or face fixing
- · Armature comes with fixing kit

Suitable Brackets/Housings:

- BKEX1200ZL (ZL bracket)
- · BKEX1200L (L bracket)

OTHER PRODUCTS

WP66-G-GB-GR



KPX50



DIMENSIONS

EXML1200-GATE-M · Monitored

SPECIFICATION

· Surface mount

· Stainless steel housing

· Built in surge protection

· +/- 15% voltage tolerance

· 545kg (1200lb) holding force

EXML1200-GATE & EXML1200-GATE-M

EXML1200-GATE & EXML1200-GATE-M

· Dual voltage 12/24 VDC @ 500/250mA

· Comes complete with 1 metre cable

· Fail safe operation (power to lock)

 \cdot -10° to +50° operating temperature

Push off release pin on armatureCOM/NO/NC Voltage free relay contacts

- · 222x61x38 (mm) Maglock
- · 195x60x14 (mm) Armature
- · 4.5kg Boxed
- · 2.85kg Unboxed

CONTENTS

EXML1200-GATE & EXML1200-GATE-M

- · External magnet
- · Armature plate
- \cdot EX1200GB fixing kit
- Instructions
- · Armature fixing template





TRANOI-RECOI





