





IP66 external range סו ווופאוטראי שויה brackets from a market leader in access control.

MAGNETIC LO



SPECIFICIATION

EXML600-GATE & EXML600-GATE-M

- · Stainless steel housing
- · 280kg (600lb) holding force
- · Dual voltage 12/24 VDC @ 500/250mA
- · Comes complete with 1 metre cable
- · Built in surge protection
- · Surface mount
- · Fail safe operation (power to lock)
- · +/- 15% voltage tolerance
- \cdot -10° to +50° operating temperature
- · Push off release pin on armature
- · Voltage free relay contacts

EXML600-GATE-M

Monitored

FEATURES

EXML600-GATE & EXML600-GATE-M

- · External magnet IP66
- Weatherproof
- · Dual voltage 12V/24V
- · Side or face fixing
- · Armature comes with fixing kit

Suitable Brackets/Housings:

BKEX600ZL (ZL bracket)

OTHER PRODUCTS

WP66-G-GB-PTO



FRANOI-RECOI



DIMENSIONS

EXML600-GATE & EXML600-GATE-M

- · 220x46x26 (mm) Maglock
- · 200x44x20 (mm) Armature
- · 2.64kg Boxed
- · 1.55kg Unboxed

CONTENTS

EXML600-GATE & EXML600-GATE-M

- · External magnet
- · Armature plate
- · EX600GB fixing kit
- Instructions
- · Armature fixing template









