


HD TAB 900 Plus

THE NEW GENERATION OF TABLET ANALYZERS





SPECIAL FUNCTIONS

- Exclusive patented ROVER AUTODISCOVERY system: automatically detects and selects analog and digital COFDM/QAM TV signals in both measurement and spectrum mode.
- NEW: Exclusive Easy navigation menu.
- **HELP function:** automatically identifies all the signals with digital modulation SAT, TV and CATV.
- Automatic Assistant: Signal Quality analysis, Channel Scan memorization.
- Barscan TV & CATV function from 10 to 100 channels on one screen.
- Buzzer & Noise Margin real time graph.
- Exclusive included APP: SAT Expert.
- MER versus CARRIER

- Reflectometric measurements APP
- LAN Interface: for remote web browser internet Monitoring with opt. APP.



ISDB-T - ATSC - GB20600



MAIN FUNCTIONS

MEASUREMENTS & SPECTRUM ANALYSIS

- **Freq. Range:** TV and CATV TUNER, extended band, 4-1250 MHz; SAT TUNER, extended band, 930-2610 MHz; GSM extended band, 860-1000 MHz for telephone repeater installation.
- Input Impedance: 75 ohm (interchangeable "F" connector).
- Digital Meas: Digital Power, MER, BER, PER, LDPC, BCH, Noise Margin, MER versus CARRIER.
- Analog Meas & Picture: Analog level, V/A ratio.
- Power range Meas.: TV 28 to 130 dBμV, SAT 30 to 130 dBμV.
- Net-id on board: Net-id, NID, TSID, LCN, SAT Orbit Position.
- Fast spectrum with MAX HOLD: full spect. capabilities with memory peak, variable span and automatic reference level.
- Constellation: for TV/CATV and SAT signals.
- Echoes, Pre-echoes, Micro-echoes: Representation in real Time.
- Quality: Digital Auto quality Test: PASS-MARGINAL-FAIL.
- **Digital Pictures:** MPEG2-4 SD & HD pictures with Program List, Audio Video PIDs, LCN, Video bit Rate all on one screen.
- TV Memory plan: World Wide countries with related channels plans pre-memorized.
- SAT Memory Plan: More than 2.000 transponders prememorized for world wide Satellite.
- Manual Memory Plan: Programmable TV, SAT (or combined TV/SAT) by PC or Local Keyboard.
- Loggers: TV, SAT & combined with stop & go function.
- Audio: AAC supplied, DOLBY (opt.).
- Optical Power meter: with SC connector for fiber optic testing (FTTH & FTTX).
- Free SMART PC interface program and FW upgrades.
- OPTIONS*: check the Cross reference on page 12.

GENERAL SPECIFICATIONS

- 9" TFT TOUCH display: 16:9 high resolution.
- DC voltage at RF input: 5 12 18 24 V, DiSEqC, SCR, dCSS.
- Battery: Li-Po battery pack, 3 h duration & Battery Test function
- Power supply & Battery charger: 12 Vdc, 2A.
- **USB PC Interface:** For SW upgrade on-line and memory plan management.
- USB PC Interface: For storage memory stick.
- Housing: Metal box and bag elite. Padded bag optional.
- Weight: only 1,8 Kg. Size: H 27,0 x W 15,5 x D 4,0 cm (meter only).
- * Some options must be requested when ordering the instrument.


Visit
WWW.ROVERSHOP.IT
to check the
available
accessories.

Features and functions may change without notice.

ICON MENU



New Icon Navigation Menu



Wide Band Measure & spectrum



Wi-Fi Analyzer



New Meas. & Pict. Super fast



New constellation diagram



SAT FINDER