HEX31WP-TX

HDMI Wall Plate HDBaseT™ Transmitter

Description


Our HEX31WP HDMI/USB-C wall plate HDBaseT™ transmitter is a multi-format 4K input switcher solution delivering HDMI and USB-C inputs up to 70m 1080p (40m 4K). The HEX31WP-TX features both manual or automated source selection and includes display on / off control via CEC, RS-232 and IR (via compatible HDBaseT™ receivers). The HEX31WP-TX has been designed to work with all Blustream HDBaseT™ receiver solutions, be installed in both UK and European backboxes and can be powered locally or from compatible Blustream HDBaseT[™] products.


Specifications

- Video Input Connectors: 2 x HDMI Type A, 19-pin, female, 1 x USB-C Type C
- Video Output Connectors: 1 x HDBaseT™ RJ45 connector
- RS-232 serial port: 1 x 3-Pin Phoenix connector
- IR Input port: 1 x 3-Pin Phoenix connector
- Product upgrade: 1 x Micro USB female
- Local power input: 1 x 2-Pin Phoenix connector
- Casing Dimensions (W x H x D): 146mm x 86mm x 44mm
- Operating Temperature: 32°F to 104°F (-5°C to +55°C)
- Storage Temperature: -4°F to 140°F (-25°C to +70°C)
- Power Supply: 12V/1A DC

Key Features

- Features 2 x HDMI & 1 x USB-C inputs with manual / auto source selection
- Advanced HDBaseT[™] technology offering distribution of video and audio over a single CAT cable
- Supports 4K UHD video up to 40m (3840 x 2160 @30Hz 4:4:4, 4096 x 2160 @24Hz 4:4:4, and 4K @60Hz 4:2:0)
- Extends HDMI 1080p up to a distance of 70m
- Supports all known HDMI audio formats including Dolby TrueHD, Dolby Atmos, Dolby Digital Plus and DTS-HD Master Audio transmission
- Input selection via front panel, IR and RS-232
- Programmable ON / OFF button utilising IR, RS-232 or CEC for control of display device at HDBaseT™ Receiver
- Supports 12V-48V PoC from compatible Blustream HDBaseT™ Matrix
- · Bi-directional RS-232 pass through
- Supports IR pass-through to HDBaseT™ Matrix or Receiver
- Compatible with all Blustream HDBaseT™ Matrix or Receivers*
- Magnetic faceplate surround allowing both UK & EU backbox compatibility
- HDCP 2.2 support
- *Technical performance is subject to the features supported on the connected HDBaseT[™] product

























Blustream cannot be held responsible for errors in typography or photography. Specifications are subject to change without notice.







