

2N® IP UNI

AFFORDABLE IP INTERCOM

The 2N® IP Uni intercom is the ideal solution for communication, in general purpose outdoor and indoor environments. Its easy operation and interface with the IP world will ensure nobody ever gets lost on the premises. In an instant it connects you with, for example, reception or security and provides you with professional assistance.



- **Stainless steel front plate**
- **Visual status signalling**
- **Built-in tamper switch**
- **Easy installation**
- **Replacement for an analogue intercom**

VARIANTS



**1 button,
pictograms**
9153101P



1 button
9153101



2 buttons
9153102

TECHNICAL PARAMETERS

Signalling protocol

SIP (UDP, TCP)

Buttons

Button design Transparent, white backlit buttons with easily replaceable name tags

Button count 1 or 2

Audio

Microphone 1 integrated microphone

Amplifier 1 W (class D)

Loudspeaker 1 W

Volume control Adjustable with automatic adaptive mode

Full duplex Yes (AEC)

Audio stream

Protocols RTP/RTSP

Codecs G.711

Interfaces

Power supply PoE or 12V / 2A DC

PoE 802.3af (Class 0 - 12.95W)

LAN 10/100BASE-TX s Auto-MDIX, RJ-45

Recommended cabling Cat-5e or higher

Passive switch NO/NC contacts, up to 30 V / 1 A AC/DC

Active switch output 8 up to 12 V DC depending on power supply (PoE: 9 V; adaptor: power supply voltage minus 2 V), max 600 mA

Mechanical properties

Cover ABS plastic, high-quality stainless steel

Operating temperature -40 °C to 55 °C

Storage temperature - 40 °C to 70 °C

Operating relative humidity 10 % to 95 % (non-condensing)

Dimensions 193 x 115 x 39 mm

197 x 119 x 47 mm

with flush mounting box

193 x 115 x 57 mm for wall mounting

Weight 500 g (Product net weight)

135 g (Mounting box)

800 g (Total weight incl. Package)

Coverage level IP54, IK10