


Product Code: MM515WH

Description: 2A USB Charging Module



General Information

Dimensions (mm)	25 (W) x 55.7 (H) x 37 (D)		
Dimensions When Installed (mm)	25 (W) x 50 (H) x 35 (D)		
Finish	White		
Materials	Cover & Housing: Polycarbonate PCB: Electronic Components	Terminals& Screws: Brass	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	230	Frequency (Hz)	50
Resistive Load Rating (A)	2		
USB Output Type	USB Type "A"		
USB Number Of Outputs	1	USB Charging Total Load (A)	2
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.4
Terminal Capacity - Solid (mm²)	2 x 1.5		
Product Marking	USB 5V 2A		
Minimum Back Box Depth (mm)	35 (47 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	1		

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 Internally fused which enables direct mains supply.