

75 SERIES Masthead Splitters · 2, 3 & 4 Output



SPECIFICATION

Product Range:	MS02LTE	MS03LTE	MS04LTE
No. of Inputs	1	1	1
No. of Outputs	2	3	4
Frequency range	470-790MHz	470-790MHz	470-790MHz
Insertion Loss	<3.5dB	<6dB	<8dB
Isolation Ports	>20dB	>30dB	>30dB
DC Pass on all ports	Input 1 x 12V 100mA		

75 Series masthead splitters enable a single television aerial to be connected to 2, 3 or 4 TV sets. Supplied in a weatherproof housing and feature a DC pass allowing the splitter to be used with a masthead amplifier if required. Can be mounted to mast or wall or soffit.



75 SERIES Masthead Splitters · 6 & 8 Output



SPECIFICATION

Product Range:	MS06LTE	MS08LTE
No. of Inputs	1	1
No. of Outputs	6	8
Frequency range	470-790MHz	470-790MHz
Insertion Loss	<12dB	<16dB
Isolation Ports	>30dB	>30dB
DC Pass on all ports	Input 1 x 12V 100mA	

Masthead splitters in the 75 Series range for larger installations. Split a single TV aerial to 6 or 8 TV sets from the tried and tested weatherproof housing. DC pass in all outputs enables use with a masthead amplifier if required. Can be mounted to mast or wall or soffit.

