



1U Rack Mounting PDU with Surge Protection & EMI Filter

1U high Horizontal Mounting Unit is designed to provide a versatile hook-up for the distribution of AC & DC power within multimedia racking applications.

Input Power Con EMI filtered input with protection against Lightning Strike & Local Power Surge.

20A T inline internal fuse.

Output AC~ 8 x IEC320 C13 in 2 banks of 4 with a Maximum Combined Load 20A

Protection 2 x 10 AMP Circuit Breaker Switches

DC PSU Switchable **Isolated** Universal DC supply fully protected

(AC input range 88V~264V)

Output DC- 12 Way Pluggable Screw Terminal Socket

3 x 5V dc 3 x 12V dc

With a Max Combined Load of 65W

Earth Link Thumb Screw Terminal for Rack Grounding

Usage

Nominal Voltage: 230V

Usable Voltages 200V~ 240V full range Frequency: 50/60HZ full range

Max. A/C Output: Current 20A

Case Size: 45 x 140 x 430mm (O.A.483mm)

Weight: 2Kg

Compliance All components used in this conform to current RoHS, CE & UL certification

(EMI:EN55022 (CISPR22) Class B; EN61000-3-2,3 EMS:EN61000-4-2,3,4,5,6,8,11; Light industry level, criteria A)



